

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0908140206](#)
Status: **Active**
Overview: [picoflex](#)
Description: 1.27mm (.050") Pitch Picoflex® PF-50 Header, Vertical, Low Profile, Surface Mount, 6 Circuits, Glow Wire Compatible

Documents:
[3D Model](#) [Product Specification PS-99020-0011 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification


UL E29179

General

Product Family PCB Headers
Series [90814](#)
Application Wire-to-Board
Application Tooling Part Link 690081070
Comments Low Profile SMT
Overview [picoflex](#)
Product Name Picoflex®

Physical

Breakaway No
Circuits (Loaded) 6
Color - Resin Black, Natural
Durability (mating cycles max) 30
First Mate / Last Break No
Flammability 94V-0
Glow-Wire Compliant Yes
Guide to Mating Part No
Keying to Mating Part None
Lock to Mating Part Yes
Material - Metal Brass
Material - Plating Mating Tin
Material - Resin High Temperature Thermoplastic
Number of Rows 1
Orientation Vertical
PCB Locator Yes
PCB Retention Yes
PCB Thickness Recommended (in) 0.062 In
PCB Thickness Recommended (mm) 1.60 mm
Packaging Type Tube
Pitch - Mating Interface (in) 0.050 In
Pitch - Mating Interface (mm) 1.27 mm
Plating min: Mating (µin) 120
Plating min: Mating (µm) 3
Plating min: Termination (µin) 120
Plating min: Termination (µm) 3
Polarized to Mating Part Yes
Polarized to PCB Yes
Shrouded No
Stackable No
Surface Mount Compatible (SMC) N/A
Temperature Range - Operating -40°C to +105°C
Termination Interface: Style Surface Mount



Series

image - Reference only

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Halogen-Free
Status

China RoHS



Need more information on product environmental compliance?
Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)
Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[90814Series](#)

Mates With
[90327 IDT Connector](#)

Application Tooling | FAQ
Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.
Global

Description	Product #
Extraction Tool (Plastic) for 90327 Connector, 4-26 Circuit	0690081070

Electrical

Current - Maximum per Contact	1.2A
Voltage - Maximum	250V

Solder Process Data

Duration at Max. Process Temperature (seconds)	3
Lead-free Process Capability	Reflow Capable (SMT only)
Max. Cycles at Max. Process Temperature	1
Process Temperature max. C	260





Material Info

Reference - Drawing Numbers


Packaging Specification	SDA-90814-9001
Product Specification	PS-99020-0011
Sales Drawing	SDA-90814

This document was generated on 06/08/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION



SECTION Y-Y



(SCALE 10:1)

NOTES:

- MATERIAL: HOUSING: NYLON 4/6 30% G.F., UL 94 V-0, NATURAL (BEIGE)
TERMINAL- CARTRIDGE BRASS (0.28)/.011 REF THICK
- PLATING:
TIN: TIN (3-5UM)/120UM-200UM OVER (1.27UM)/5UM MIN NICKEL.
GOLD: (0.76UM)/30UM SELECTIVE GOLD AND
(0.10-0.20UM)/4UM-8UM GOLD FLASH OVER (1.27UM)/50UM
NICKEL UNDERCOAT
- MATES WITH MOLEX 90327 PART SERIES
- ALL SMT TAILS TO LIE WITHIN A COPLANARITY BAND OF
(0.0)/.0 - (0.10)/.004 REF. FROM EACH OTHER.
- FOR TAPE & REEL PACKAGING DETAILS SEE SDA-90814-9001
- PCB PEGS ARE OPTIONAL
- PCB LAYOUT SHOWN ON SHEET 2

90814 - **

CIRCUIT SIZE

	PCB PEGS	TUBE PACKED	TAPE & REEL PACKED	POLARIZING PEG HEIGHT DIMN. E
0	YES	YES	NO	(6.40)/ .252
2	YES	NO	YES	(6.40)/ .252
3	NO	YES	NO	(6.40)/ .252
5	NO	NO	YES	(6.40)/ .252
6	NO	YES	NO	(4.10)/ .161
7	NO	NO	YES	(4.10)/ .161
8	YES	YES	NO	(4.10)/ .161
9	YES	NO	YES	(4.10)/ .161

0= (3-5UM)/120-200UM TIN VERSION

3= (0.76UM)/30UM GOLD VERSION

90814--34	34	(46.96)/.1849	(41.91)/.1650	(45.76)/.1802	10	NO
90814--26	26	(36.80)/.1449	(31.75)/.1250	(35.60)/.1402	14	YES
90814--24	24	(34.26)/.1349	(29.21)/.1150	(33.06)/.1302	15	YES
90814--22	22	(31.72)/.1249	(26.67)/.1050	(30.52)/.1202	16	YES
90814--20	20	(29.18)/.1149	(24.13)/.0950	(27.98)/.1102	18	YES
90814--18	18	(26.64)/.1049	(21.59)/.0850	(25.44)/.1002	20	YES
90814--16	16	(24.10)/.0949	(19.05)/.0750	(22.90)/.0902	22	YES
90814--14	14	(21.56)/.0849	(16.51)/.0650	(20.36)/.0802	25	YES
90814--12	12	(19.02)/.0749	(13.97)/.0550	(17.82)/.0702	28	YES
90814--10	10	(16.48)/.0649	(11.43)/.0450	(15.28)/.0602	32	YES
90814--08	8	(13.94)/.0549	(8.89)/.0350	(12.74)/.0502	38	YES
90814--06	6	(11.40)/.0449	(6.35)/.0250	(10.20)/.0402	46	YES
90814--04	4	(8.86)/.0349	(3.81)/.0150	(7.66)/.0302	60	YES
PART NO.	NUMBER OF CKTS	DIMN. A	DIMN. B	DIMN. C	QUANTITY OF PARTS PER TUBE (-0**/-3**/-6** & -8** VERSIONS)	TOOLED

REDUCED CO-PL TOL
EC NO: E2007-0304
DRAWN: JENNEY 2006/11/07
CHKD: JENNEY 2006/11/07
APPR: JENNEY 2006/11/13

QUALITY
SYMBOLS
=0
=0




GENERAL TOLERANCES
(UNLESS SPECIFIED)
mm INCH
4 PLACES ± --- ± ---
3 PLACES ± --- ± .004
2 PLACES ± 0.10 ± ---
1 PLACE ± --- ± ---
ANGULAR ±1/2°
DRAFT WHERE APPLICABLE
MUST REMAIN
WITHIN DIMENSIONS

DIMENSION STYLE
MM/IN
DRAWN BY DATE
DMCNAMAR 2001/08/16
CHECKED BY DATE
PCURTIN 2001/08/16
APPROVED BY DATE
MWILHITE 2001/08/16
MATERIAL NO.
DOCUMENT NO.
SDA-90814

SCALE
5:1

DESIGN UNITS
METRIC

THIRD ANGLE
PROJECTION
PICO FLEX
SMT HEADER
MOLEX INCORPORATED
SHEET NO.
1 OF 2

[illegible]