



SPECIFICATION:
Current Rating: 2.0AMP
Contact Resistance: 20m Ω (max)
Insulation Resistance: 1000M Ω Min at 500V DC
Dielectric Strength: 500V AC Per 1 Minute
Operating Temperature: -40°C TO +105°C

MATERIALS:
Insulator: Nylon 6T Glass Fibre (UL 94V-0)
Contact: Brass
Contact plated: Gold Over Nickel

CONTACTS	PART NO.	A	B	C
10	310-2S-10P	10.0	25.9	8.0
12	310-2S-12P	12.0	27.9	10.0
14	310-2S-14P	14.0	29.9	12.0
16	310-2S-16P	16.0	31.9	14.0
20	310-2S-20P	20.0	35.9	18.0
22	310-2S-22P	22.0	37.9	20.0
24	310-2S-24P	24.0	39.9	22.0
26	310-2S-26P	26.0	41.9	24.0
30	310-2S-30P	30.0	45.9	28.0
32	310-2S-32P	32.0	47.9	30.0
34	310-2S-34P	34.0	49.9	32.0
40	310-2S-40P	40.0	55.9	38.0
44	310-2S-44P	44.0	59.9	42.0
50	310-2S-50P	50.0	65.9	48.0

TOLERANCE TABLE

.0	±0.30
.00	±0.20
.000	±0.05

APPROVED:	DATE:	TITLE: 310-2S-XP 长耳			
CHECKED:	DATE:	CLIENT P/N B-3102SXXP-A000			
DRAWN: YAN	DATE: 2011-12-12	UNIT mm	SCALE Free		
		FILE NO. ChamtW-310-00010		REV. A	

深圳市灿科盟实业有限公司
CHANKEMENG INDUSTRY CO., LTD