SHEET 1 OF 1



CIRCUIT: DPDT 3-WAY

NOTE: JUMPER PIN 3 TO PIN 5

SWITCH FUNCTION		
POS. 1	POS. 2	POS. 3
ON	ON	ON
2-3,5-6	2-3,5-4	2-1,5-4





VIEW A-A





NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
   X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 5A @120VAC OR 28VDC
   2A @250VAC
5. MATERIALS: FIXED TERM. &MOVING CONTACT:
   Cu Alloy w/Silver plate
6. ELECTRICAL LIFE: 50,000 make-and-break
   cycles at full load.
7. INSULATION RESISTANCE: 1,000M ohm min.
8. DIELECTRIC STRENGTH: 1000V RMS @sea level
9. OPERATING TEMP.: -30°C to 85°C

REV.	ECN No.	DESCRIPTION	DATE	CHKD
A	13078	RELEASED FOR PRODUCTION	4/24/03	AR

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E-SWITCH®

TITLE: 100DP6T1B1M2QE

SCALE	DATE	DR	DWG	REV
2:1	4/24/03	AR	T126063	A