


Power Divider



Plug-in

A1

E2

2-way 90° Narrowband 5 to 900MHz

P/N	Freq. Range (MHz) f _o	Insertion Loss (dB) Typ/Max	Isolation (dB) Typ/Min	VSWR Typ	Unbalance		Case
					Phase (°) Max	Amp. (dB) Max	
JXWBGF-A-2-90-10.2-11.2	10.2-11.2	0.2/0.3	25/20	1.2	3	0.8	A1
JXWBGF-A-2-90-20.4-22.4	20.4-22.4	0.2/0.3	25/20	1.2	3	0.8	A1
JXWBGF-A-2-90-57-63	57-63	0.2/0.3	25/20	1.2	3	0.8	A1
JXWBGF-A-2-90-427.5-472.5	427.5-472.5	0.2/0.6	25/17	1.3	3	0.9	A1
JXWBGF-E-2-90-4.75-5.25	4.75-5.25	0.3	25/20	1.1	3	0.7	E2
JXWBGF-E-2-90-28.5-31.5	28.5-31.5	0.3	25/20	1.1	3	0.7	E2
JXWBGF-E-2-90-57-63	57-63	0.3	25/20	1.1	3	0.7	E2
JXWBGF-E-2-90-56.5-63.5	56.5-63.5	0.3	25/20	1.1	3	0.7	E2
JXWBGF-E-2-90-152-168	152-168	0.3	25/17	1.2	3	0.7	E2
JXWBGF-E-2-90-855-945	855-945	0.3	25/15	1.3	3	0.9	E2

Notes: 1. Operating Temperature : -40°C to +80°C. Storage Temperature : -55°C to +85°C.

2-way 90° 3.2 to 1000MHz

P/N	Freq. Range (MHz) f _L -f _U	Insertion Loss (dB) Typ/Max	Isolation (dB) Typ/Min	VSWR Typ	Unbalance		Case
					Phase (°) Max	Amp. (dB) Max	
JXWBGF-A-2-90-3.2-6.4	3.2-6.4	0.2/0.5	25/20	1.2	3	1.8	A1
JXWBGF-A-2-90-6-12	6-12	0.3/0.7	25/20	1.2	3	1.0	A1
JXWBGF-A-2-90-7-14	7-14	0.3/0.7	25/20	1.2	3	1.0	A1
JXWBGF-A-2-90-8-16	8-16	0.3/0.7	25/20	1.2	3	1.0	A1
JXWBGF-A-2-90-10-20	10-20	0.3/0.7	25/20	1.2	3	1.0	A1
JXWBGF-A-2-90-12-25	12-25	0.3/0.7	25/20	1.2	3	1.0	A1
JXWBGF-A-2-90-15-30	15-30	0.3/0.7	25/20	1.2	3	1.0	A1
JXWBGF-A-2-90-20-40	20-40	0.3/0.7	25/20	1.2	3	1.0	A1
JXWBGF-A-2-90-25-50	25-50	0.3/0.7	25/20	1.2	3	1.5	A1
JXWBGF-A-2-90-30-60	30-60	0.3/0.7	25/20	1.2	3	1.5	A1
JXWBGF-A-2-90-35-70	35-70	0.3/0.7	25/20	1.2	3	1.5	A1
JXWBGF-A-2-90-40-80	40-80	0.3/0.7	25/20	1.2	3	1.5	A1
JXWBGF-A-2-90-55-90	55-90	0.3/0.7	25/20	1.2	3	1.5	A1
JXWBGF-A-2-90-50-100	50-100	0.3/0.8	25/20	1.2	3	1.5	A1
JXWBGF-A-2-90-66-74	66-74	0.2/0.3	25/20	1.2	0.8	0.25	A1
JXWBGF-A-2-90-80-120	80-120	0.3/0.7	25/20	1.2	3	1.5	A1
JXWBGF-A-2-90-100-160	100-160	0.3/0.7	25/20	1.2	3	1.5	A1
JXWBGF-A-2-90-120-180	120-180	0.3/0.7	25/20	1.2	3	1.5	A1
JXWBGF-A-2-90-120-240	120-240	0.4/0.8	25/20	1.2	3	1.5	A1
JXWBGF-A-2-90-150-250	150-250	0.4/0.8	25/20	1.3	3	1.5	A1
JXWBGF-A-2-90-150-300	150-300	0.4/0.8	25/20	1.3	4	1.5	A1
JXWBGF-A-2-90-250-400	250-400	0.5/0.9	23/16	1.3	4	1.5	A1
JXWBGF-A-2-90-350-450	350-450	0.3/0.9	23/16	1.3	5	1.5	A1
JXWBGF-A-2-90-450-550	450-550	0.5/0.9	19/15	1.3	5	1.5	A1
JXWBGF-A-2-90-550-1000	550-1000	0.3/0.6	25/20		3	1.5	A1
JXWBGF-A-2-90-20-60	20-60	0.8/1.0	23/20	1.3	3	1.2	A1
JXWBGF-A-2-90-30-90	30-90	0.8/1.2	23/18	1.3	3	1.2	A1
JXWBGF-A-2-90-10-50	10-50	0.8/1.0	25/20	1.5	3	1.0	A1
JXWBGF-A-2-90-20-100	20-100	0.8/1.0	25/20	1.5	3	1.0	A1
JXWBGF-A-2-90-60-300	60-300	0.9/1.2	25/18	1.5	4	1.0	A1
JXWBGF-A-2-90-3-32	3-32	1.0/1.5	25/20	1.5	4	1.5	A1
JXWBGF-A-2-90-25-250	25-250	1.3/1.8	25/17	1.5	6	1.5	A1
JXWBGF-A-2-90-50-500	50-500	1.7/2.0	25/17	1.5	7	1.5	A1

Notes: 1. Operating Temperature : -40°C to +80°C. Storage Temperature : -55°C to +85°C.