TAI-SAW TECHNOLOGY CO., LTD.
No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.
TEL: 886-3-4690038 FAX: 886-3-4697532
E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Name: SAW Filter 1815 MHz (BW 50 MHz) SMD 3.0X3.0 mm

TST Parts No.: TA2561A

Customer Parts No.:_____

Company:_____

Division:_____

Approved by :_____

Date:_____

Checked by:_____ Sam Lin _____

Approval by:_____ Andy Yu _____

Date:_____ 2019/05/22 _____

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes

TAI-SAW TECHNOLOGY CO., LTD.
No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.
TEL: 886-3-4690038 FAX: 886-3-4697532
E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 1815 MHz (BW 50 MHz) SMD 3.0X3.0 mm

MODEL NO.:TA2561A REV. NO.:1.0

A. MAXIMUM RATING:

1. Input Power Level: 15 dBm
2. DC Voltage : 0 V
3. Operating Temperature: -45℃ to +85℃
4. Storage Temperature: -45℃ to +85℃

RoHS Compliant
Lead free
Lead-free soldering

Electrostatic **S**ensitive **D**evice (**ESD**)

B. ELECTRICAL CHARACTERISTICS:

Terminating source impedance (single) : Zs = 50 Ω

Terminating load impedance(single) : Z_L = 50 Ω

Item	**Unit**	Min	Typ.	Max
Center Frequency	MHz	-	1815	-
Insertion Loss (1790~1840 MHz)	dB	-	2.7	3.5
Insertion Loss (1780~1850 MHz)	dB	-	3.8	5.5
Attenuation (Reference from 0 dB)				
10 ~ 1750 MHz	dB	27	30	-
1750 ~ 1770 MHz	dB	5	18	-
1870 ~ 1930 MHz	dB	10	23	-
1930 ~ 3000 MHz	dB	30	35	-
Temperature Coefficient of Frequency	ppm/K	-	-36	-

C. TEST CIRCUIT:



D. OUTLINE DRAWING:



△ : Year Code (2009->9, 2010->0,…, 2018->8)

□ : Date Code (Follow the table from planner each year)

WK01	WK02	WK03	WK04	WK05	WK06	WK07	WK08	WK09	WK10	WK11	WK12	WK13
A	B	C	D	E	F	G	H	I	J	K	L	M
WK14	WK15	WK16	WK17	WK18	WK19	WK20	WK21	WK22	WK23	WK24	WK25	WK26
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
WK27	WK28	WK29	WK30	WK31	WK32	WK33	WK34	WK35	WK36	WK37	WK38	WK39
a	b	c	d	e	f	g	h	i	j	k	l	m
WK40	WK41	WK42	WK43	WK44	WK45	WK46	WK47	WK48	WK49	WK50	WK51	WK52
n	o	p	q	r	s	t	u	v	w	x	y	z

E. Frequency Characteristics:

Span 800 MHz



Span 3000 MHz



Span 100 MHz



Reflection Characteristic



F. PCB FOOTPRINT:



G. PACKING:

1. REEL DIMENSION
(Please refer to FR-75D10 for packing quantity)



2. TAPE DIMENSION



H. RECOMMENDED REFLOW PROFILE :

1. Preheating shall be fixed at 150~180℃ for 60~90 seconds.
2. Ascending time to preheating temperature 150℃ shall be 30 seconds min.
3. Heating shall be fixed at 220℃ for 50~80 seconds and at 260℃+0/-5℃ peak (20~40sec).
4. Time: 2 times.