


ENERGIZER NO. EN92



Industry Standard Dimensions in mm (inches)




AAA

NOT INTENDED FOR RETAIL TRADE

Chemical System:	Alkaline Zinc-Manganese Dioxide (Zn/MnO ₂) (No Added Mercury or Cadmium)
Designation:	ANSI-24A, IEC-LR03
Battery Voltage:	1.5 Volts
Internal Resistance:	205 Milliohms (Fresh)
Operating Temp:	-18°C to 55°C (0°F to 130°F)
Average Capacity:	1,250 mAh (to 0.8 volts) (Rated capacity at 25 mA continuous drain)
Average Weight:	11.5 grams (0.4 oz.)
Volume:	3.8 cubic centimeters (0.2 cubic inch)
Cell:	One No. 3-312 (size 'AAA')
Jacket:	Plastic Label
Shelf Life:	7 years (80% of rated capacity)


TEMPERATURE EFFECTS

Typical Service to 0.8 Volts




CONSTANT RESISTANCE PERFORMANCE

Typical Service



CONSTANT CURRENT DISCHARGE

Typical Service



Important Notice


This data sheet contains information specific to batteries manufactured at the time of its publication.

Contents herein do not constitute a warranty.


Copyright © Eveready Battery Co. - All rights reserved

ENERGIZER NO. EN92

CONSTANT POWER DISCHARGE
Typical Service




CONSTANT POWER DISCHARGE
Typical Service




Industry Standard Tests @ 20° C

LIGHTING
5.1 ohm - 4 min/hr 8 hr/day




PHOTOFLASH
600 mA - 10 sec/min 1 hr/day



REMOTE
24 ohm - 15 spm - 8 hr/day



TAPE - ELECTRONIC GAMES-DIGITAL AUDIO
100 mA - 1 hr/day



Important Notice

This data sheet contains information specific to batteries manufactured at the time of its publication.

Contents herein do not constitute a warranty.

Copyright © Eveready Battery Co. - All rights reserved