



For and on behalf of
KKB INDUSTRIAL PRECISION CO., LIMITED
香港星坤工業精密有限公司

■ Specifications :

- Voltage rating: 350V AC / DC
- Current rating: 3A AC / DC
- Withstanding voltage: 500V AC/minute
- Temperature range: -55°C~+105°C
- Insulation resistance: ≥1000MΩ
- Contact resistance: ≤20mΩ
- After environmental testing: ≤40mΩ

X1511 H -XX -PT

① ② ③ ④

- ① Series No.
- ② Category: H-HSG
- ③ Row No.-Pin No.: XX-02P~15P
- ④ Material: PT-PBT 94V-0

Poles	Dimensions (mm)			Poles	Dimensions (mm)		
	A	B	C		A	B	C
02	1.50	3.30	3.70	09	12.00	13.80	14.20
03	3.00	4.80	5.20	10	13.50	15.30	15.70
04	4.50	6.30	6.70	11	15.00	16.80	17.20
05	6.00	7.80	8.20	12	16.50	18.30	18.70
06	7.50	9.30	9.70	13	18.00	19.80	20.20
07	9.00	10.80	11.20	14	19.50	21.30	22.10
08	10.50	12.30	12.70	15	21.00	22.80	23.60

X1511H-XX-PT	PBT 94V-0	X1511T	X1511W
PART NO	Material	Suitable XKB Terminal	Suitable XKB Terminal

REVISIONS					UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE: Connectors		
△ X	Authorized Signature(s)				ANGULAR			VIEW:	PART NO.: X1511H-XX-PT		
△ X					L ≤ 4			UNIT: mm	DWG NO.: X1511H-XX-PT		
△ X					4 < L ≤ 16			SIZE: A4			
MARK	DESCRIPTION	DATE	REVISED	APPROVED	16 < L ≤ 63						
					L > 63				WEIGHT	SHEET	REVISION
									1.0g	1/1	A0

KKB INDUSTRIAL PRECISION CO., LIMITED