General Cable Product Data Sheet

RoHS Compliant Directive 2002/95/EC

Part Number: C1308 Revision Level: 3 Date: 11/14/2007

5C 20 AWG 26/34 TC RUBBER OAS RUBBER **CONTROL CABLE**

A. CONSTRUCTION

		DIAMETERS
Conductor:	#20 AWG 26/34 Tinned Copper	0.038" nom.
Insulation:	0.020" Wall Rubber	0.080" nom.
Cable:	5 conductors @ 2.50" LHL with jute fillers & mylar wrap.	0.230" nom.
Braid	#36 AWG Tinned Copper 80% min. coverage	0.250" nom.
Tape:	Cotton Separator	0.260" nom.
Jacket:	0.035" Wall Rubber - Black	0.330" +/- 0.017"
Print Legend:	***CAROL (R) C-1308A MADE IN USA***	

B. INDUSTRY APPROVALS

NONE

C. ELECTRICAL PROPERTIES

TEMPERATURE:	60 C
SUGGESTED WORKING VOLTAGE (Vrms):	300Vrms
CONDUCTOR D.C. RESISTANCE:	11.3 Ohms/1000 ft nom

D. COLOR CODE *(Listed as Individual Conductors or Pairs of Conductors)*

1	Black
2	White
3	Red
4	Green
5	Blue

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.