



HCMOS 32.768kHz 3.2x2.5mm Oscillator

O3HK

(former FK315, FK345, FK335 Series)

DATASHEET

- HCMOS Output
- Stabilities to ± 20 PPM
- Temperature Ranges as wide as -20°C to $+70^{\circ}\text{C}$
- Supply Voltages: 1.8V; 2.5V; 3.3V

1.8V ELECTRICAL CHARACTERISTICS

PARAMETERS	MAX (unless otherwise noted)
Frequency (F_0)	32.768 kHz
Storage Temperature Range (T_{STG})	$-55 \sim +125^{\circ}\text{C}$
Supply Voltage (V_{DD})	$1.8\text{V} \pm 10\%$
Input Current (I_{DD})	120 μA
Standby Current	10 μA
Output Symmetry (50% V_{DD})	45% ~ 55%
Rise/Fall Time (10%-90% V_{DD} Levels) ($T_{\text{R}}/T_{\text{F}}$)	50 ns
Output Voltage (V_{OL})	10% V_{DD}
(V_{OH})	90% V_{DD} Min
Output Load (HCMOS)	15 pF
Start-up Time (T_{S})	2 mS
Output Disable Time ¹	1 μS
Output Enable Time ¹	2 mS

ENABLE / DISABLE FUNCTION

Pin1	Output (pin 3)
OPEN ¹	Active
'1' Level $V_{\text{IH}} \geq 70\%V_{\text{DD}}$	Active
'0' Level $V_{\text{IL}} \leq 30\%V_{\text{DD}}$	High Z

Frequency Stability	Operating Temperature ($^{\circ}\text{C}$)
$\pm 50\text{PPM}^2$	$-20 \sim +70$
$\pm 50\text{PPM}^2$	$-40 \sim +85$
$\pm 25\text{PPM}^2$	$-20 \sim +70$
$\pm 25\text{PPM}^3$	$-40 \sim +70$
$\pm 20\text{PPM}^3$	$-10 \sim +60$

¹ An internal pull-up resistor from pin 1 to pin 4 allows active output if pin 1 is left open

² Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, reflow, one-year aging, shock, and vibration.

³ Inclusive of 25°C tolerance, operating temperature range.





HCMOS 32.768kHz 3.2x2.5mm Oscillator

O3HK

(former FK315, FK345, FK335 Series)

DATASHEET

- HCMOS Output
- Stabilities to ± 20 PPM
- Temperature Ranges as wide as -40°C to $+85^{\circ}\text{C}$
- Supply Voltage: 1.8V; 2.5V; 3.3V

2.5V ELECTRICAL CHARACTERISTICS

PARAMETERS	MAX (unless otherwise noted)
Frequency (F_o)	32.768 kHz
Storage Temperature Range (T_{STG})	$-55 \sim +125^{\circ}\text{C}$
Supply Voltage (V_{DD})	$2.5\text{V} \pm 10\%$
Input Current (I_{DD})	126 μA
Standby Current	10 μA
Output Symmetry ($50\%V_{DD}$)	45% ~ 55%
Rise/Fall Time ($10\%-90\%V_{DD}$ Levels) (T_R/T_F)	50 nS
Output Voltage (V_{OL}) (V_{OH})	90% V_{DD} 10% V_{DD} Min
Output Load (HCMOS)	15 pF
Start-up Time (T_S)	2 mS
Output Disable Time ¹	1 μS
Output Enable Time ¹	2 mS

ENABLE / DISABLE FUNCTION

Pin1	Output (pin 3)
OPEN ¹	Active
'1' Level $V_{IH} \geq 70\%V_{DD}$	Active
'0' Level $V_{IL} \leq 30\%V_{DD}$	High Z

Frequency Stability	Operating Temperature ($^{\circ}\text{C}$)
$\pm 50\text{PPM}^2$	$-20 \sim +70$
$\pm 50\text{PPM}^2$	$-40 \sim +85$
$\pm 25\text{PPM}^2$	$-20 \sim +70$
$\pm 25\text{PPM}^3$	$-40 \sim +70$
$\pm 20\text{PPM}^3$	$-10 \sim +60$

¹ An internal pull-up resistor from pin 1 to pin 4 allows active output if pin 1 is left open

² Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, reflow, one-year aging, shock, and vibration.

³ Inclusive of 25°C tolerance, operating temperature range.





HCMOS 32.768kHz 3.2x2.5mm Oscillator

O3HK

(former FK315, FK345, FK335 Series)

DATASHEET

- HCMOS Output
- Stabilities to ± 20 PPM
- Temperature Ranges as wide as -40°C to $+85^{\circ}\text{C}$
- Supply Voltages: 1.8V; 2.5V; 3.3V

3.3V ELECTRICAL CHARACTERISTICS

PARAMETERS	MAX (unless otherwise noted)
Frequency (F_o)	32.768 kHz
Storage Temperature Range (T_{STG})	$-55 \sim +125^{\circ}\text{C}$
Supply Voltage (V_{DD})	$3.3V \pm 10\%$
Input Current (I_{DD})	130 μA
Standby Current	10 μA
Output Symmetry ($50\%V_{DD}$)	45% ~ 55%
Rise/Fall Time ($10\%-90\%V_{DD}$ Levels) (T_R/T_F)	50 nS
Output Voltage (V_{OL})	10% V_{DD}
(V_{OH})	90% V_{DD} Min
Output Load (HCMOS)	15 pF
Start-up Time (T_S)	2 mS
Output Disable Time ¹	1 μS
Output Enable Time ¹	2 mS

ENABLE / DISABLE FUNCTION

Pin1	Output (pin 3)
OPEN ¹	Active
'1' Level $V_{IH} \geq 70\%V_{DD}$	Active
'0' Level $V_{IL} \leq 30\%V_{DD}$	High Z

Frequency Stability	Operating Temperature ($^{\circ}\text{C}$)
$\pm 50\text{PPM}^2$	$-20 \sim +70$
$\pm 50\text{PPM}^2$	$-40 \sim +85$
$\pm 25\text{PPM}^2$	$-20 \sim +70$
$\pm 25\text{PPM}^3$	$-40 \sim +85$
$\pm 20\text{PPM}^3$	$-10 \sim +60$

¹ An internal pull-up resistor from pin 1 to pin 4 allows active output if pin 1 is left open

² Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, reflow, one-year aging, shock, and vibration.

³ Inclusive of 25°C tolerance, operating temperature range.






HCMOS 32.768kHz 3.2x2.5mm Oscillator

O3HK
(former FK315, FK345, FK335 Series)
DATASHEET

DIMENSIONS / MECHANICAL SPECIFICATIONS

Mechanical / Dimensions:



Dimensions are in millimeters

Pin Connections

#1 E/D #3 Output
#2 GND #4 VDD

Maximum Soldering Temp / Time	260°C / 10 Seconds x 2
Moisture Sensitivity Level (MSL)	1
Termination Finish	Au over Ni
Seal Method	Seam
Lead (Pb) Free	Yes
ROHS/REACH Compliant	Yes

Notes:

A 0.01µF capacitor should be placed between V_{DD} (Pin 4) and GND (Pin2) to minimize power supply line noise.
Dimensional drawing is for reference to critical specifications defined by size measurements.
Certain non-critical visual attributes, such as side castellations, reference pin shape, etc. may vary



© Copyright 2020 Fox Electronics. All rights reserved

Title / Description: O3HK SERIES STANDARD SPECIFICATIONS

Drawing Number: O3HK-DOC-1

Size: A

Part Number:

Cage: 61429

Draftsperson: BEC

Approved: MAJ

Revision Date: 03/09/2019




HCMOS 32.768kHz 3.2x2.5mm Oscillator

O3HK

(former FK315, FK345, FK335 Series)

DATASHEET

Tape Specifications (millimeters)							Reel Specifications (millimeters)						
A	B	C	D	E	F	Reel Qty	G	H	I	J	K	L	M
Ø1.5	4.0	4.0	3.5	8.0	1.4	-T3 = 3,000 -T2 = 2,000 -T1 = 1,000	2.5	Ø13	Ø22	Ø60	Ø178	8.0	1.6



Available Options & Part Identification

Example: **F O3HK C B M 0.032768**

F	O3HK	C	D	M	0.032768
Fox	Model Number	Voltage C = 3.3V ±10% J = 2.5V ±10% L = 1.8V ±10%	Stability B = ±50 PPM D = ±25 PPM E = ±20 PPM	Operating Temperature D = -10C ~ +60°C F = -20C ~ +70°C M = -40C ~ +85°C	Frequency



Corporate Headquarters

5570 Enterprise Parkway
Fort Myers, FL 33905
<http://www.FOXONLINE.com>

Sales

1-888-GET-2-FOX (1-888-438-2369)
or
1-239-693-0099
<http://www.FOXONLINE.com/repdisty>

Tech Support

<http://www.FOXONLINE.com/email>

Product use: Fox Electronics reserves the right to modify the products and/or specifications described herein at any time and at Fox Electronics' sole discretion. All information in this document, including descriptions of product features and performance, is subject to change without notice. Performance specifications and the operating parameters of the described products are determined in the independent state and are not guaranteed to perform the same way when installed in customer products. The information contained herein is provided without representation or warranty of any kind, whether express or implied, including, but not limited to, the suitability of Fox Electronics' products for any particular purpose, an implied warranty of merchantability, or non-infringement of the intellectual property rights of others. This document is presented only as a guide and does not convey any license under intellectual property rights of Fox Electronics or any third parties.

Fox Electronics' products are not intended for use in applications involving extreme environmental conditions or in life support systems or similar devices where the failure or malfunction of a Fox Electronics product can be reasonably expected to significantly affect the health or safety of users. Anyone using a Fox Electronics product in such a manner does so at their own risk, absent an express, written agreement by Fox Electronics.

Fox Electronics and the Fox logo are registered trademarks of Fox Electronics. Product specification is subject to change without notice. Other trademarks and service marks used herein, including protected names, logos and designs, are the property of Fox Electronics or their respective third-party owners.



© Copyright 2020 Fox Electronics. All rights reserved

Title / Description: O3HK SERIES STANDARD SPECIFICATIONS

Drawing Number: O3HK-DOC-1

Size: A

Part Number:

Cage: 61429

Draftsperson: BEC

Approved: MAJ

Revision Date: 03/09/2019