# Product data sheet Characteristics

# 8502SBO2V02SX11

NEMA Contactor, Type S, nonreversing, Size 0, 18A, 5 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 120 VAC coil, open

Product availability: Non-Stock - Not normally stocked in distribution facility





#### Main

Product Type	Contactor	
Туре	8502S	
Control Circuit Type	Separate control circuit	
Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz	
Contactor Type	Non-reversing	
Current Rating	18 A	
Number of Poles	3P	
Phase	3 phase	
Horsepower Rating	3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC	:
Maximum Voltage Rating	600 V AC	
SCCR	Circuit-breaker 70 A maximum, SCCR: 100 kA at 480 V AC Fuse J 60 A maximum, SCCR: 100 kA at 600 V AC Fuse T 60 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 60 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 60 A maximum, SCCR: 100 kA at 600 V AC	
Control Units	No control units	
Pilot Light	No indicator	
Auxiliary Contacts	1 NO + 1 NC	
Control Circuit Fusing	Fuse not supplied	
Electrical Connection	Screw clamp terminals	
Enclosure Type	Not rated (open device)	
Certifications	UL listed file E78351 CCN NLDX CSA	

NEMA Size	0	
Height	4.34 in (110.24 mm)	
Depth	4.22 in (107.19 mm)	
Width	3.73 in (94.79 mm)	

### Ordering and shipping details

Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
Nbr. of units in pkg.	1
Package weight(Lbs)	4 lb(US) (1.81 kg)
Returnability	No
Country of origin	MX

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Not compliant	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	

#### Contractual warranty

Warranty	18 months	