




Specifications:

- Voltage rating: 250V AC/DC
- Current rating: 3A AC/DC
- Withstanding voltage: 800V AC/minute
- Temperature range: -25 °C ~ +85 °C
- Insulation resistance: $\geq 1000M\Omega$
- Contact resistance: $\leq 20m\Omega$
- After environmental testing: $\leq 20m\Omega$

X2509 T M-P SN

① ② ③ ④ ⑤

- ① XKB Series No.
- ② Category: T-terminal
- ③ M: male
- ④ Material: P-Phosphor bronze
- ⑤ Plating Category : SN-Bright Tin Plating



X2509TM-PSN	Phosphor bronze	AWG#22-28	1.2~1.9mm(Max)	Stamping Before Pating:30u"Ni MIN;70" Sn MIN	X2509HF
PART NO	Material	Wire Range	Insulation O.D.	Finish	Suitable XKB Terminal

DSND		DATE		SCALE: N/A	MODEL TYPE: X2509TM-PSN
DWN		DATE		VIEW:	PART NO.:
CHKD		DATE		UNIT: mm/in	DWG NO.:
APPD		DATE		SIZE: A4	
				XKB INDUSTRIAL PRECISION CO.,LIMITED	WEIGHT 1.0g
					SHEET 1/1
					REVISION A0

XKB	ANGLAR	$\pm 5^\circ$
	$L \leq 4$	± 0.2
	$4 < L \leq 16$	± 0.3
	$16 < L \leq 63$	± 0.4
	$L > 63$	± 0.5
UNSPECIFIED TOLERANCES		

REVISIONS	DESCRIPTION	DATE	REVISED	APPROVED
www.helloxkb.com				