




4

10

9 X 2.5 = 22.5

2.5 TYP

-X- ⚠

BSC ⚠

BSC ⚠

-Y- ⚠

1.5 TYP

ROW A

ROW B

ROW BG (GROUND)

ROW C

ROW D

ROW DG (GROUND)

ROW E

ROW F

ROW FG (GROUND)

ROW G

ROW H

ROW HG (GROUND)

10

6

5

1

⌀0.05Ⓢ X Y

ALL PLATED THRU HOLES

RECOMMENDED PC BOARD LAYOUT, BACKPLANE, COMPONENT SIDE SHOWN

SCALE 4:1

⚠ REFERENCE APPLICATION SPEC 114-13059 FOR RECOMMENDED PLATED THRU HOLE DIAMETER AND PLATING THICKNESSES.

⚠ MATERIAL:
CONTACT AND SHIELD - PHOSPHOR BRONZE
HOUSING - GLASS FILLED POLYESTER. UL 94V-0.

⚠ FINISH: SIGNAL AND GROUND CONTACTS:
MATING AREA: MEETS THE PERFORMANCE REQUIREMENTS OF PRODUCT SPECIFICATION 108-2055; BASED ON TELCORDIA GR-1217-CORE, APPLICATIONS IN UNCONTROLLED ENVIRONMENTS
COMPLIANT PIN AREA: 0.5 µm MIN MATTE TIN OVER BASE PLATING

⚠ CONNECTOR MARKED WITH PART NUMBER AND DATE CODE.

⚠ DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.

⚠ THE FOUR GROUNDS IN EACH COLUMN ARE COMMONED.

7. CONTACT AREA LUBRICATED WITH BELLCORE APPROVED LUBRICANT. TECHNICAL REFERENCE: GR-1217-CORE, ISSUE 1, NOVEMBER 1995.

⚠ DIMENSION APPLIES TO FIRST AND LAST CIRCUITS.

⚠ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

⚠ TE OR TE CONNECTIVITY LOGO IS LOCATED.

⚠	OBSOLETE	3.80	6469074-2
		5.30	6469074-1
		DIM M	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S. J. MAGARO 28JUN2004	TE Connectivity	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		CHK R. A. PATTERSON 28JUN2004		
DIMENSIONS:	mm	APVD R. PATTERSON 16AUG2007	NAME	
		0 PLC	PRODUCT SPEC	
		1 PLC	APPLICATION SPEC	
		2 PLC	SIZE	
		3 PLC	CAGE CODE	
MATERIAL		4 PLC	DRAWING NO	
ANGLES		FINISH	RESTRICTED TO	
2		3	A100779C=6469074	
CUSTOMER DRAWING		WEIGHT	REV C	
		SCALE 8:1	SHEET 1 OF 1	