


Sales Region	Worldwide (except Japan)
Series	ALE
Model	ALE-Rack mount
Status	 Production
Option	Negative polarity
Option Lineup	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics

Input	3-phase
Input Voltage Range[AC]	340 to 460VAC
Input Frequency Range	47 to 63Hz
Rated Output Voltage[DC]	10000Vdc
Output Voltage Range[DC]	0 to 10000V
Average Capacitor Charging Power	30000J/sec
Peak Capacitor Charging Power	37500J/sec
Charge Current	7.5A
Continuous DC Current	5A
Continuous DC Power	40kW
Polarity	Negative
Power Factor	0.9
Efficiency	85% Typ.

Package Type & Size

Package / Mounting	Rack mount
Width(W)	482mm Nom. (18.98in Nom.)
Height(H)	311mm Nom. (12.24in Nom.)
Depth(D)	571mm Nom. (22.48in Nom.)
Weight	100kg Typ. (220.5lbs Typ.)

Other

Operating Temp. Range	0 to 55°C
Storage Temp. Range	-40 to 70°C
Cooling	Water
Safety Standard(Certified)	
Safety Standard(Conformed)	

Remarks This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.