







Verpackt im Gurt nach DIN IEC 60286-3
Tape on Reel Packaging according to DIN IEC 60286-3
Verpackungseinheit: 280 Stück
Packaging unit: 280 pcs




ohne Ansaughaube - without hood



Abspulrichtung - Reel off Direction



Leiterplatten-Layout Vorschlag für SMT
PCB-Layout Proposal for SMT



Anforderungsstufe 1
Performance Level 1

Kontaktbereich vergoldet
Mating Area gold plating

Anschlussbereich verzinkt 4-6 µm
Terminal Area 4-6 µm tin plating

Koplanarität der Anschlüsse ≤ 0,1 mm
Coplanarity Area of Termination ≤ 0,1 mm

BA 7-03 - Standard Bauhöhe

type 7-03 - standard assembly height

Copyright by ERNI GmbH
Proprietary notice pursuant to ISO 16045 to be observed.

Information:				Tolerances		 All Dimensions in mm		Scale 3:1				
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.				Subject to modification without prior notice. Drawing will not be updated.				Designation				
								Federl. SMC-B 12-SMD-BA7-03 <i>Female SMC-B 12-SMD-type7-03</i>				
				e		04.12.2013				www.ERNI.com		154717
Index		Date						Class		SMCB		A3

Copyright by ERNI GmbH
Proprietary notice pursuant to ISO 16018 to be observed.