


SMD ■ B

EAST1615RW01



Features

- Package in 8mm tape on 7" diameter reel.
- Compatible with automatic placement equipment.
- Compatible with infrared and vapor phase reflow solder process.
- Multi -color type.
- Pb-free.
- The product itself will remain within RoHS compliant version.
- Compliance with EU REACH.
- Compliance Halogen Free .(Br <900 ppm ,Cl <900 ppm , Br+Cl < 1500 ppm).

Description

- The SMD LED is much smaller than lead frame type components, thus enable smaller board size, higher packing density, reduced storage space and finally smaller equipment to be obtained.

- Besides, lightweight makes them ideal for miniature applications. etc.

Applications

- Backlighting in dashboard and switch.
- Telecommunication: indicator and backlighting in telephone and fax.
- Flat backlight for LCD, switch and symbol.
- General use.

Device Selection Guide

Code	Chip Materials	Emitted Color	Resin Color
R6	AlGaInP	Brilliant red	Yellow Diffused
T1	InGaN	Pure White	

Absolute Maximum Ratings (Ta=25°C)

Parameter	Symbol	Code	Rating	Unit
Reverse Voltage	V_R		5	V
Forward Current	I_F	R6	25	mA
		T1	10	
Peak Forward Current (Duty 1/10 @1KHz)	I_{FP}	R6	60	mA
		T1	100	
Power Dissipation	P_d	R6	60	mW
		T1	40	

Operating Temperature	T _{opr}	-40 ~ +85	°C
Storage Temperature	T _{stg}	-40 ~ +90	°C
Electrostatic Discharge	ESD _{HBM}	R6	2000
		T1	150
Soldering Temperature	T _{sol}	Reflow Soldering : 260 °C for 10 sec. Hand Soldering : 350 °C for 3 sec.	

Electro-Optical Characteristics (Ta=25°C)

Parameter	Symbol	Code	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	I_v	R6	18.0	----	45.0	mcd	
		T1	45.0	----	112.0		
Viewing Angle	$2\theta_{1/2}$		----	140	----	deg	
Peak Wavelength	λ_p	R6	----	632	----	nm	
		T1	----	----	----		
Dominant Wavelength	λ_d	R6	621.5	----	633.5	nm	$I_F=5mA$
		T1	----	----	----		
Spectrum Radiation Bandwidth	$\Delta\lambda$	R6	----	17	----	nm	
		T1	----	----	----		
Forward Voltage	V_F	R6	1.55	----	2.15	V	

		T1	2.70	-----	3.30		
		R6	-----	-----	10		
Reverse Current	I_R					μA	$V_R=5V$
		T1	-----	-----	50		

Note:

1. Tolerance of Luminous Intensity: $\pm 11\%$
2. Tolerance of Dominant Wavelength: $\pm 1nm$
3. Tolerance of Forward Voltage: $\pm 0.1V$

EVERLIGHT

Bin Range of Luminous Intensity

R6

Bin Code	Min.	Max.	Unit	Condition
M	18.0	28.5	mcd	$I_F = 5\text{mA}$
N	28.5	45.0		

Bin Range of Luminous Intensity

T1

Bin Code	Min.	Max.	Unit	Condition
P	45.0	72.0	mcd	$I_F = 5\text{mA}$
Q	72.0	112.0		

Bin Range Of Dom. Wavelength

R6

Bin Code	Min.	Max.	Unit	Condition
E5	621.50	625.50	nm	$I_F = 5\text{mA}$
E6	625.50	629.50		
E7	629.50	633.50		

Bin Range Of Forward Voltage

R6

	Bin Code	Min.	Max.	Unit	Condition
A	00	1.55	1.75	V	$I_F = 5\text{mA}$
	0	1.75	1.95		
	1	1.95	2.15		

T1

	Bin Code	Min.	Max.	Unit	Condition
--	----------	------	------	------	-----------

K	10	2.70	2.90	V	$I_F = 5\text{mA}$
	11	2.90	3.10		
	12	3.10	3.30		

Note:

1. Tolerance of Luminous Intensity: $\pm 11\%$
2. Tolerance of Dominant Wavelength: $\pm 1\text{nm}$
3. Tolerance of Forward Voltage: $\pm 0.1\text{V}$

Chromaticity Coordinates Specifications for Bin Grading

T1


Groups	Bin Code	CIE_x	CIE_y	Condition
C	1	0.274	0.226	$I_F = 5\text{mA}$
		0.274	0.258	
		0.294	0.286	
		0.294	0.254	
	2	0.274	0.258	
		0.274	0.291	
		0.294	0.319	
		0.294	0.286	
	3	0.294	0.254	
		0.294	0.286	
		0.314	0.315	
		0.314	0.282	
	4	0.294	0.286	
		0.294	0.319	
		0.314	0.347	
		0.314	0.315	

Notes:

1. The C.I.E. 1931 chromaticity diagram (Tolerance ± 0.01).
2. The products are sensitive to static electricity and care must be fully taken when handling products.

CIE Chromaticity Diagram
T1


EVERLIGHT




Typical Electro-Optical Characteristics Curves

R6


Spectrum Distribution




Forward Current vs.
Forward Voltage




Luminous Intensity vs.
Ambient Temperature




Luminous Intensity vs
Forward Current



Radiation Diagram $T_a = 25^\circ\text{C}$









Forward Current Derating Curve





Typical Electro-Optical Characteristics Curves

T1






Polarity



Recommend soldering pad



Suggested pad dimension is just for reference only.
Please modify the pad dimension based on individual need.

11 Copyright © 2010, Everlight Americas Inc. All Rights Reserved. Release Date : 28-Mar-2015 .
Issue No: DSE-0012980 Rev:2


Moisture Resistant Packing Materials

Label Explanation



- CPN: Customer's Product Number
- P/N: Product Number
- QTY: Packing Quantity
- CAT: Luminous Intensity Rank
- HUE: Chromaticity Coordinates & Dom. Wavelength Rank
- REF: Forward Voltage Rank
- LOT No: Lot Number


Reel Dimensions



Note: The tolerances unless mentioned is $\pm 0.1\text{mm}$,Unit = mm


EVERLIGHT

Carrier Tape Dimensions: Loaded quantity 2000 PCS per reel



Note: The tolerances unless mentioned is $\pm 0.1\text{mm}$, Unit = mm

Moisture Resistant Packaging



Precautions For Use

1. Over-current-proof

Customer must apply resistors for protection, otherwise slight voltage shift will cause big current change (Burn out will happen).

2. Storage

2.1 Do not open moisture proof bag before the products are ready to use.

2.2 Before opening the package: The LEDs should be kept at 30°C or less and 90%RH or less.

2.3 After opening the package: The LED's floor life is 1 year under 30°C or less and 60% RH or less.


If unused LEDs remain, it should be stored in moisture proof packages.

2.4 If the moisture absorbent material (silica gel) has faded away or the LEDs have exceeded the storage time, baking treatment should be performed using the following conditions.

Baking treatment : 60±5°C for 24 hours.

3. Soldering Condition

3.1 Pb-free solder temperature profile



3.2 Reflow soldering should not be done more than two times.

3.3 When soldering, do not put stress on the LEDs during heating.


3.4 After soldering, do not warp the circuit board.

4. Soldering Iron

Each terminal is to go to the tip of soldering iron temperature less than 350°C for 3 seconds within once in less than the soldering iron capacity 25W. Leave two seconds and more intervals, and do soldering of each terminal. Be careful because the damage of the product is often started at the time of the hand solder.

5. Repairing

Repair should not be done after the LEDs have been soldered. When repairing is unavoidable, a double-head soldering iron should be used (as below figure). It should be confirmed beforehand whether the characteristics of the LEDs will or will not be damaged by repairing.



Application Restrictions

High reliability applications such as military/aerospace, automotive safety/security systems, and medical equipment may require different product. If you have any concerns, please contact everlightamericas before using this product in your application. This specification guarantees the quality and performance of the product as an individual component. Do not use this product beyond the specification described in this document.

EVERLIGHT