

Han 24HPR enlarged-HTE-SCL-M32-FE



Image is for illustration purposes only. Please refer to product description.

Part number	19 40 024 0442
Specification	Han 24HPR enlarged-HTE-SCL-M32-FE
HARTING eCatalogue	https://b2b.harting.com/19400240442

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] HPR
Type of hood/housing	Hood
Description of hood/housing	Enlarged with functional earth

Version

Locking type	Screw locking
Size	24 B
Version	Top entry
Cable entry	1x M32
Field of application	Hoods/housings for harsh outdoor environments

Technical characteristics

Tightening torque (screw locking)	4 Nm
Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP66 IP68 IP69 / IPX9K acc. to ISO 20653
Type rating acc. to UL 50 / UL 50E	4 4X 12



Pushing Performance

Material properties

Material (hood/housing)	Aluminium die-cast Corrosion resistant
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 9005 (jet black)
Material (locking)	Stainless steel

Specifications and approvals

Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
CE	Yes

Commercial data

Packaging size	1
Net weight	796 g
Country of origin	China
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors