

**X-RAY
IMAGING**

X-CUBE™ **COMPACT X-RAY CCD CAMERAS**

H8480/H8481/H8953 Series

SAMPLE X-RAY IMAGES


Sample: Cellular phone substrate

X-ray tube voltage: 90 kV, Geometrical magnification rate: $\times 1.15$

H8480


(Wide View Type)

Effective view: $\phi 25$ mm Min.
Resolution : 10 Lp/mm Typ.



H8953


Effective view: 16.7 mm $\times$ 12.5 mm
Resolution : 16 Lp/mm Typ.



H8481

(High Resolution Type)

Effective view: 8.4 mm $\times$ 6.3 mm
Resolution : 20 Lp/mm Typ.



OVERVIEW

X-CUBE is a compact X-ray CCD camera designed for nondestructive inspection. Using a general-purpose CCD chip mounted in a rugged but lightweight camera head, X-CUBE makes X-ray imaging as easy as handling ordinary CCD cameras.

The H8480 has a large effective view of 25 mm diameter and a resolution of 10 Lp/mm, while the H8953 has an effective view of 16.7 mm $\times$ 12.5 mm and a resolution of 16 Lp/mm, while the H8481 offers an effective view of 8.4 mm $\times$ 6.3 mm and a high resolution of 20 Lp/mm.



▲Left: H8480, Center: H8953, Right: H8481


FEATURES

- High sensitivity: CsI scintillator
- Compact
- Low power consumption

SAMPLE X-RAY IMAGES

●Low Energy

H8480



▲Seeds
X-ray tube voltage: 25 kV
Geometrical magnification rate: $\times 2.1$


H8481



▲Seeds
X-ray tube voltage: 25 kV
Geometrical magnification rate: $\times 2.1$


●High Magnification

H8481



▲Bonding wire
X-ray tube voltage: 80 kV
Geometrical magnification rate: $\times 3.5$


H8481



▲Diode
X-ray tube voltage: 80 kV
Geometrical magnification rate: $\times 7.5$


●Others

H8953




▲Lithium-ion battery
X-ray tube voltage: 95 kV
Geometrical magnification rate: $\times 2.8$

H8953



▲High voltage cable
X-ray tube voltage: 70 kV
Geometrical magnification rate: $\times 2.5$

H8953



▲Reference mark in multi-layer printed circuit board
X-ray tube voltage: 50 kV
Geometrical magnification rate: $\times 3.3$

SPECIFICATIONS

GENERAL RATINGS


Parameter	H8480-13	H8480-14	H8953-13	H8953-14	H8481-15	H8481-16
Effective View	$\phi 25$ mm Min.		16.7 mm $\times$ 12.5 mm		8.4 mm $\times$ 6.3 mm	
Resolution	10 Lp/mm Typ.		16 Lp/mm Typ.		20 Lp/mm Typ.	
TV Method	EIA ①	CCIR ②	EIA ①	CCIR ②	EIA ①	CCIR ②
Imaging Sensor	Interline transfer 2/3-inch CCD image sensor					
Number Of Pixels	768 (H) $\times$ 494 (V)	752 (H) $\times$ 582 (V)	768 (H) $\times$ 494 (V)	752 (H) $\times$ 582 (V)	768 (H) $\times$ 494 (V)	752 (H) $\times$ 582 (V)
Scanning Method	Interlace/ Non-interlace					
Sync. Method	Internal / External (auto selection by the input signal)					
External Sync. Signal Input / Output	S. VS (SYNC level 0.3 V), HD/VD (2 V to 5 V)					
Video Signal Output	1.0 V p-p (negative sync., 75 Ω , unbalanced)					
Power Supply Voltage (DC)	+12.0 V (range: 10.5 V to 15 V)					
Power Consumption	Approx.2.1 W					
γ Correction	0.45/1.0 (selected by switch on the rear panel)					
Gain	AGC/FIX/MANUAL (selected by switch on the rear panel)					
Shutter Speed	1/125 s to 1/10 000 s (selected by switch on the rear panel)					
Operating Ambient Temperature	-5 $^{\circ}$ C to 45 $^{\circ}$ C					
Storage Temperature	-10 $^{\circ}$ C to 60 $^{\circ}$ C					
Operating Ambient Humidity	Below 80 % (no condensation)					

①EIA: Electronic Industries Association


②CCIR : Comite Consultatif Internationale des Ratio Communications

CONNECTION EXAMPLE

●Camera Adapter




●AC Adapter




DIMENSIONAL OUTLINE (Unit: mm)

H8480




TXPRA0016EA

H8953



TXPRA0017EA

H8481



TXPRA0018EA

Subject to local technical requirements and regulations, availability of products included in this promotional material may vary. Please consult with our sales office. Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions. Specifications are subject to change without notice. No patent rights are granted to any of the circuits described herein. ©2013 Hamamatsu Photonics K.K.

HAMAMATSU PHOTONICS K.K. www.hamamatsu.com

HAMAMATSU PHOTONICS K.K., Electron Tube Division

314-5, Shimokanzo, Iwata City, Shizuoka Pref., 438-0193, Japan, Telephone: (81)539/62-5248, Fax: (81)539/62-2205

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P. O. Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1)908-231-0960, Fax: (1)908-231-1218 E-mail: usa@hamamatsu.com

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49)8152-375-0, Fax: (49)8152-2658 E-mail: info@hamamatsu.de

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trappu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: (33)1 69 53 71 00, Fax: (33)1 69 53 71 10 E-mail: infos@hamamatsu.fr

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road Welwyn Garden City Hertfordshire AL7 1BW, United Kingdom, Telephone: 44-(0)1707-294888, Fax: 44-(0)1707-325777 E-mail: info@hamamatsu.co.uk

North Europe: Hamamatsu Photonics Norden AB: Thorshamnsgatan 35 SE-164 40 Kista, Sweden, Telephone: (46)8-509-031-00, Fax: (46)8-509-031-01 E-mail: info@hamamatsu.se

Italy: Hamamatsu Photonics Italia: S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39)02-935 81 733, Fax: (39)02-935 81 741 E-mail: info@hamamatsu.it

China: Hamamatsu Photonics (China) Co., Ltd.: 1201 Tower B, Jiaming Center, 27 Dongsanhuan Road North, Chaoyang District, Beijing 100020, China, Telephone: (86)10-6586-6006, Fax: (86)10-6586-2866 E-mail: hpc@hamamatsu.com.cn

TXPR1020E01
FEB. 2013 IP