

## High Value Multilayer Ceramic Capacitors (High dielectric type)

## JMK021BJ472KK-W



## ■ Features

- Item Summary  
4700pF±10%, 6.3V,  
X5R, 008004/0201 (EIA/JIS)
- Lifecycle Stage  
Mass Production
- Standard packaging quantity (minimum)  
Taping Embossed 50000pcs

## ■ Products characteristics table

Capacitance	4700 pF ± 10 %
Case Size (EIA/JIS)	008004/0201
Rated Voltage	6.3 V
tan δ (max)	10 %
Temperature Characteristic (EIA)	X5R
Operating Temp. Range (EIA)	-55 to +85 °C
High Temperature Loading (% Rated Voltage)	150 %
Insulation Resistance (min)	10 MΩ · μF
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (168 subst.)	Yes
Soldering	Reflow

## ■ External Dimensions

Dimension L	0.25 ± 0.013 mm
Dimension W	0.125 ± 0.013 mm
Dimension T	0.125 ± 0.013 mm
Dimension e	0.0675 ± 0.0275 mm





2016.12.06

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.  
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.  
 Before making final selection, please check product specification.

## ○JMK021BJ472KK

6.3V 0201 X5R 4700pF +/- 10% t=0.138mmMAX

6.3V 008004 X5R 4700pF +/- 10% t=0.0054inchMAX



部品特性は設置環境、測定条件等により変化する場合があります。本データをご使用される際は実際の製品特性に対する参考データとしてご活用ください。また、本データは予告無く追加・削除及び変更を行う場合があります。ご注文の際は、納入仕様書のご確認をお願いします。

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.

TAIYO YUDEN reserves the right to make change to the data at any time without notice.

Before making final selection, please check product specification.