


NT

Screw Terminal Type, Wide Temperature Range
series



- Load life of 5,000 hours (2,000 hours for 10~250V, 500V) application of rated ripple current at +105°C.
- Extended voltage range from 10V up to 500V.
- Extended range up to $\phi 100 \times 250L$ 2size.
- Available for adapted to the RoHS directive (2002/95/EC).




Specifications

Item	Performance Characteristics											
Category Temperature Range	- 40 ~ +105°C (10~100V) , - 25 ~ +105°C (160~500V)											
Rated Voltage Range	10 ~ 500V											
Rated Capacitance Range	220 ~ 1500000μF											
Capacitance Tolerance	± 20% at 120Hz, 20°C											
Leakage Current	After 5 minutes' application of rated voltage, leakage current is not more than 3/√CV (μA) or 5mA, whichever is smaller. (at 20°C) [C:Rated Capacitance (μF) , V:Voltage(V)]											
tan δ (MAX)	Measurement frequency:120Hz, Temperature:20°C											
	φD	V	10	16	25	35	50	63	80	100	160~250	250~500
			35	80~100	0.65	0.45	0.4	0.3	0.25	0.25	0.2	0.12
	51	80~100	0.9	0.6	0.5	0.4	0.25	0.25	0.2	0.15	0.15	0.2
		120	0.85	0.6	0.5	0.4	0.3	—	—	—	—	0.2
	63.5	100	—	—	0.65	—	0.35	0.3	0.25	0.2	0.2	0.2
		110~130	1.2	0.8	0.7	0.5	0.35	0.3	—	—	0.2	0.2
	76.2	100	2.0	1.2	0.9	0.7	0.55	0.5	0.3	0.3	—	0.2
		120~150	2.0	1.2	0.9	0.7	0.55	0.5	0.35	0.3	0.2	0.2
	90	140~220	2.4	2.0	1.5	1.0	0.75	0.6	0.4	0.3	0.25	0.2
100	220,250	2.4	2.0	1.5	1.0	0.75	0.6	0.4	0.3	0.25	0.2	
Stability at Low Temperature	Rated voltage(V)				10~100		160~500		Measurement frequency : 120Hz			
	Impedance ratio		Z - 25°C/Z+20°C		—		8					
	ZT/Z20(MAX.)		Z - 40°C/Z+20°C		12		—					
Endurance	After an application of DC voltage (in the range of rated DC voltage even after over-lapping the specified ripple current) for 5000 hours (2000 hours for 10~250V,500V) at 105°C, capacitors meet the characteristic requirements listed at right.						Capacitance change		Within ±20% of initial value			
							tan δ		300% or less of initial specified value			
							Leakage current		Initial specified value or less			
Shelf Life	After storing the capacitors under no load at 105°C for 1000 hours, and after performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they will meet the requirements listed at right.						Capacitance change		Within ±20% of initial value			
							tan δ		300% or less of initial specified value			
							Leakage current		Initial specified value or less			
Marking	Printed with white color letter on black sleeve.											


Drawing

$\phi 35$ Screw terminal type




Type numbering system

Voltage 250V or less (Example : 250V 3300 μ F)



Voltage 350V or more (Example : 450V 2200 μ F)






※ Configuration

Cr (III) Plating (RoHS compliant)	Cr (VI) Plating
SE	SM

Resin bushing available upon request.


※ Please contact to us if PVC less products are required.

● Dimension table in next page.

Screw terminal type for $\phi 51$ and largerMethod to mount resin bushing ($\phi 76.2$) (Apply to L=150 or more)Method to mount resin bushing ($\phi 90$) (Apply to L=150 or more)

※B

3-leg brackets for $\phi 90$ capacitors have different hole shapes from the ordinary ones as illustrated below.



● Dimension of terminal pitch (W) and length (ℓ) and Nominal dia. of bolt (mm)

φD	W	ℓ	α	Nominal of bolt
51	22.0	6	3	M5
63.5	28.6	6	3	M5
76.2	31.8	6	3	M5
90	31.8	6	3	M5
100	41.5	10	4	M8

● Dimensions of mounting bracket (mm)

Symbol	3-Legs					2-Legs			
	51	63.5	76.2	90	100	51	63.5	76.2	90
P	32.5	38.1	44.5	50.8	56.3	33.2	40.5	46.5	53
A	38.5	43	49.2	58.5	62	40	46.5	53	59
T	7.5	8.0	7.0	8.0	8.0	6.0	7.0	6.0	6.0
S	5.0	5.0	5.0	5.0	5.0	4.5	4.5	4.5	4.5
U	12	14	14	18	16	14	14	14	14
θ°	60	60	60	60	60	30	30	30	30
H	20	25	30	35	36	25	35	35	35
h	15	20	24	25	30	15	20	20	20

■ Dimensions

V(Code)		10V (1A)		16V (1C)		25V (1E)		35V (1V)	
Surge		13V		20V		32V		44V	
Cap.(μF)	Code	Case size φD×L (mm)	Rated ripple	Case size φD×L (mm)	Rated ripple	Case size φD×L (mm)	Rated ripple	Case size φD×L (mm)	Rated ripple
10000	103							35×80	4.7
15000	153							35×80	5.1
22000	223					35×80	4.9	35×100	5.6
33000	333	35×80	4.8	35×80	5.2	35×100	6.2	51×80	7.4
47000	473	35×100	6.2	35×100	6.8	51×80	8.3	51×100	8.4
68000	683	51×80	6.8	51×80	7.1	51×120	10.2	51×120	12.3
100000	104	51×100	8.6	51×100	9.6	63.5×100	11.5	63.5×120	13.6
150000	154	51×120	10.8	51×120	11.0	63.5×120	13.8	76.2×120	15.1
220000	224	63.5×120	13.2	63.5×120	14.1	76.2×120	17.0	90×140	17.4
330000	334	76.2×120	15.8	76.2×120	20.6	90×140	20.8	90×170	21.3
470000	474	90×140	17.0	90×140	22.1	90×170	22.4	90×220	25.4
680000	684	90×170	18.4	90×170	24.0	90×220	24.2	100×250	27.5
1000000	105	90×220	20.1	90×220	26.1	100×220	26.4		
1500000	155	100×220	22.1	100×250	28.8				

Rated Ripple (Arms) at 105°C 120Hz

■ Dimensions

V(Code)		50V (1H)		63V (1J)		80V (1K)		100V (2A)	
Surge		63V		79V		100V		125V	
Cap.(μF)	Code	Case size φD×L (mm)	Rated ripple	Case size φD×L (mm)	Rated ripple	Case size φD×L (mm)	Rated ripple	Case size φD×L (mm)	Rated ripple
2200	222							35×80	2.4
3300	332							35×80	3.3
4700	472					35×80	3.5	35×100	3.8
6800	682					35×100	3.9	51×80	5.2
10000	103	35×80	4.9	35×100	5.0	51×80	5.4	51×100	6.7
15000	153	35×100	5.5	51×80	5.9	51×100	6.4	63.5×100	7.8
22000	223	51×80	6.3	51×100	6.9	63.5×100	8.4	76.2×100	9.9
33000	333	51×120	8.0	63.5×100	9.4	76.2×100	9.9	76.2×140	12.7
47000	473	63.5×100	9.9	63.5×120	11.2	76.2×120	13.4	90×140	17.0
68000	683	63.5×120	12.8	76.2×120	13.5	90×140	17.0	90×170	18.2
100000	104	76.2×120	16.8	90×140	17.8	90×170	18.6	90×220	20.6
150000	154	90×140	19.5	90×170	21.0	90×220	21.6	100×220	23.4
220000	224	90×170	22.0	90×220	23.7	100×250	24.8		
330000	334	90×220	24.3	100×250	26.1				
470000	474	100×250	26.1						

V(Code)		160V (2C)		200V (2D)		250V (2E)	
Surge		200V		250V		300V	
Cap.(μF)	Code	Case size φD×L (mm)	Rated ripple	Case size φD×L (mm)	Rated ripple	Case size φD×L (mm)	Rated ripple
680	681					35×80	1.4
1000	102	35×80	1.6	35×80	1.7	35×100	1.9
1500	152	35×80	2.1	35×100	2.3	51×80	2.4
2200	222	35×100	2.7	51×80	2.9	51×100	3.2
3300	332	51×80	3.8	51×100	3.9	63.5×100	4.3
4700	472	51×100	4.5	63.5×100	5.1	63.5×120	5.9
6800	682	63.5×100	6.8	63.5×120	7.0	76.2×120	7.1
10000	103	63.5×120	7.8	76.2×120	8.2	90×140	9.6
15000	153	76.2×120	9.8	76.2×140	10.4	90×170	12.7
22000	223	76.2×140	12.5	90×140	15.1	90×220	15.4
33000	333	90×140	13.4	90×220	16.6	100×250	17.0
47000	473	90×220	17.2	90×250	19.9		
68000	683	100×250	19.2				

V(Code)		350V (2V)		400V (2G)		450V (2W)		500V (2H)	
Surge		400V		450V		500V		550V	
Cap.(μF)	Code	Case size φD×L (mm)	Rated ripple	Case size φD×L (mm)	Rated ripple	Case size φD×L (mm)	Rated ripple	Case size φD×L (mm)	Rated ripple
220	221			35×80	1.6	35×80	1.8		
330	331	35×80	2.1	35×80	2.3	35×100	2.4	51×80	2.7
470	471	35×80	2.8	35×100	3.1	51×80	3.4	51×80	3.2
680	681	51×80	4.1	51×80	4.2	51×100	4.4	51×100	4.2
1000	102	51×80	6.5	51×80	6.6	51×100	7.0	51×120	5.5
1500	152	51×100	8.6	51×120	9.1	51×120	9.2	63.5×110	7.1
2200	222	51×120	11.0	63.5×100	11.5	63.5×110	11.8	63.5×130	9.3
2700	272	63.5×100	12.7	63.5×110	13.1	63.5×130	13.8	63.5×150	11.0
						76.2×110	14.5	76.2×130	11.0
3300	332	63.5×110	14.4	63.5×130	15.4	63.5×150	16.5	63.5×170	12.9
						76.2×130	17.1	76.2×150	13.0
3900	392	63.5×130	16.8	63.5×150	17.9	63.5×170	18.3		
				76.2×110	18.2			76.2×150	14.1
4700	472	63.5×150	19.8	63.5×170	20.7			76.2×190	17.2
		76.2×120	19.7	76.2×130	20.3	76.2×150	21.7	90×150	16.3
		63.5×170	22.7						
5600	562	76.2×130	22.2	76.2×150	23.7	76.2×190	26.4		
						90×150	24.1	90×150	17.8
6800	682	76.2×150	26.2	76.2×170	27.6				
				90×150	26.9	90×170	28.3	90×170	20.7
8200	822	76.2×170	30.3						
		90×150	29.3	90×170	31.0	90×190	32.5	90×220	25.5
10000	103	90×150	32.4	90×190	32.9	90×220	35.1	90×250	29.9
12000	123	90×190	36.0	90×220	38.3	90×230	39.2		
15000	153	90×220	42.9	100×220	44.5	90×250	45.6		
22000	223	100×250	48.0						

Rated Ripple (Arms) at 105°C 120Hz

● Frequency coefficient of rated ripple current

Frequency (Hz)		60	120	360	1k	10k~
Coeff.	10~100V	0.90	1.00	1.08	1.15	1.15
	160~250V	0.88	1.00	1.08	1.15	1.20
	350~500V	0.82	1.00	1.20	1.35	1.40