

Part Number: BLY93A
 Description: BJTs, Si NPN Power HF




The RF Line

NPN SILICON RF POWER TRANSISTOR

... designed primarily for wideband large-signal amplifier stages in the 125-175 MHz frequency range.

- Specified 28 Volt, 175 MHz Characteristics –
 Output Power = 40 Watts
 Minimum Gain = 7.6 dB
 Efficiency = 60%
- Characterized from 125 to 175 MHz
- Includes Series Equivalent Impedances

**40 W – 175 MHz
 RF POWER
 TRANSISTOR
 NPN SILICON**




STYLE 1:
 PIN 1. EMITTER
 2. BASE
 3. EMITTER
 4. COLLECTOR

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	9.40	9.78	0.370	0.385
B	8.13	8.38	0.320	0.330
C	17.02	20.07	0.670	0.790
D	5.46	5.97	0.215	0.235
E	1.78	—	0.070	—
J	0.08	0.18	0.003	0.007
K	12.45	—	0.490	—
L	1.40	1.78	0.055	0.070
M	45° NOM		45° NOM	
P	—	1.27	—	0.050
R	7.59	7.80	0.299	0.307
S	4.01	4.52	0.158	0.178
T	2.11	2.54	0.083	0.100
U	2.49	3.35	0.098	0.132

***MAXIMUM RATINGS**

Rating	Symbol	Value	Unit
Collector-Emitter Voltage	V _{CEO}	35	V _{dc}
Collector-Base Voltage	V _{CB}	65	V _{dc}
Emitter-Base Voltage	V _{EB}	4.0	V _{dc}
Collector Current – Continuous	I _C	5.0	A _{dc}
Total Device Dissipation @ T _C = 25°C Derate above 25°C	P _D	60 342	Watts mW/°C
Operating and Storage Junction Temperature Range	T _{J, T_{stg}}	-65 to +200	°C

*Indicates JEDEC Registered Data.




Part Number: BLY93A
 Description: BJTs, Si NPN Power HF

***ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted.)**

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Collector-Emitter Breakdown Voltage (Note 1) (I _C = 200 mA _{dc} , I _B = 0)	V _{(BR)CEO}	35	-	-	V _{dc}
Collector-Emitter Breakdown Voltage (I _C = 200 mA _{dc} , V _{BE} = 0)	V _{(BR)CES}	65	-	-	V _{dc}
Emitter-Base Breakdown Voltage (I _E = 10 mA _{dc} , I _C = 0)	V _{(BR)EBO}	4.0	-	-	V _{dc}
Collector Cutoff Current (V _{CB} = 30 V _{dc} , I _E = 0)	I _{CBO}	-	-	1.0	mA _{dc}
ON CHARACTERISTICS					
DC Current Gain (I _C = 500 mA _{dc} , V _{CE} = 5.0 V _{dc})	h _{FE}	5.0	-	-	-
DYNAMIC CHARACTERISTICS					
Output Capacitance (V _{CB} = 30 V _{dc} , I _E = 0, f = 0.1 to 1.0 MHz)	C _{ob}	-	45	65	pF
FUNCTIONAL TEST					
Common Emitter Amplifier Power Gain (Figure 1) (P _{out} = 40 Watts, V _{CE} = 28 V _{dc} , f = 175 MHz)	G _{pE}	7.6	8.1	-	dB
Collector Efficiency (Figure 1) (P _{out} = 40 Watts, V _{CE} = 28 V _{dc} , f = 175 MHz)	η	60	-	-	%

Note 1: Pulsed through 25 mH inductor.
 *Indicates JEDEC Registered Data.

FIGURE 1 - 175 MHz TEST CIRCUIT SCHEMATIC



- C1, C2, C3, C4 ARCO 464 25-280 pF
- C5 0.1 μF
- L1 1" Straight #14 AWG
- L2 1 Turn #16 AWG, 1/4" I.D.
- L3 0.22 μH

