Product data sheet
Characteristics

HRL36100M73
Motor circuit protector, PowerPact H, 100A, 3 pole, 600V, 100kA

Price** : 2,028.00 USD



Main

Product or component type	Motor Circuit Protector
Range of product	PowerPact H
Trip Unit Type	Electronic
Breaking capacity code	R

Complementary

Line Rated Current	100 A
Number of Poles	3P
Interrupt Rating	200 kA 240 V AC 200 kA 480 V AC 100 kA 600 V AC
[Ue] rated operational voltage	600 V AC
Continuous current rating	80 %
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
Wire Gauge	AWG 14...AWG 3/0 aluminium/copper
Magnetic hold current	180 A
Magnetic tripping current	1300 A
Maximum Height	6.4 in (162.56 mm)
Width	4.12 in (104.65 mm)
Depth	4.36 in (110.74 mm)

Environment

Product certifications	CE CSA IEC UL Listed

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	CCC
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	01127-HL, JL UNT MNT MTR CIRCUIT PROTECTR
Discount Schedule	DE2
Package weight(Lbs)	5.00 lb(US) (2.268 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.