


ZWS150BAF-15/L



Sales Region	Worldwide
Series	ZWS-BAF
Status	Production
Feature	
Option	With chassis model
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics

Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 370V
Efficiency	89% Typ.
Rated Output Voltage[DC]	15V
Output Voltage Range[DC]	13.5 to 16.5V
Maximum Output Current	10A
Maximum Output Power	150W

Cases Shape & Size

Case'□ shape	PC board
Width(W)	85mm Nom.
Height(H)	47mm Nom.
Depth(D)	188mm Nom.
Weight	560g Typ.

Other

Operating Temp. Range	-10 to 70°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1
	CSA C22.2 No.60950-1
	EN60950-1
Safety Standard(Conformed)	EN50178 (OV II)
	Den-an
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.