PASTERNACK ENTERPRISES®
PO Box 16759. Irvine, CA 92623-6759

Toll Free: (866) 727-8376
Direct: +1 (949) 261-1920
FAX: +1 (949) 261-7451
Email: sales@pasternack.com

PE51088
Mini Omni Antenna
2400-2500 & 4900-5825 MHz
2.0 dBi



Product Features

- Mini Rugged Antenna- with white/grey Radome
- 2400-2500 and 4900-5825 Freq Range
- 2.0 dBi Omni Radiation Pattern

Description

The PE51088 Mini Rugged Dual Band Antenna provides excellent performance in multiple wireless applications. Its small size and rugged construction is perfect for both indoor and portable wireless systems.

Specifications (1)

Parameter	Value	Units	Description
Band 1 Frequency	2400-2500	MHz	
Band 2 Frequency	4900-5825	MHz	
Impedance	50	Ohms	
Gain	2	dBi	
Polarization	O	Omni	
RF Power Rating	25	W	Max
Maximum VSWR	<2.0:1	ratio	Between 2.4-2.5 GHz
Maximum VSWR	<3.0:1	ratio	Between 4.9-5.1 GHz
Maximum VSWR	<2.5:1	ratio	Between 5.1-5.825 GHz
Length	90.7	mm	3.6 Inches
Diameter	14.5	mm	.57 Inch
Connector Type		RP TNC(m)	Reverse Polarity TNC Male

Ordering Information

Part Number	Description
PE51088	Mini Omni Grey Radome, 90.7mm Dia X 14.5mm, Reverse Polarity TNC Male, 2400-2500 MHz | 4900-5825 MHz, 2.0 dBi

(1) Pasternack reserves the right to change specifications or information without notice.
(2) All Specifications "Typical" values