



XKB: 2.54[0.100]±0.10

A±0.20

广东星坤科技股份有限公司

生
發

日
期

文件工程章

REVISIONS

www.xkpcb.cn www.hellixkb.com www.hellixkb.cn

ANGLR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5

UNSPECIFIED TOLERANCES

Specifications:

規格:
Voltage rating: 250V AC/DC
额定电压: 250V AC/DC
Current rating: 2A AC/DC
额定电流: 2A AC/DC
Withstanding voltage: 1500V AC/minute
耐压电压: 1500V AC/分钟
Temperature range: -25°C ~ +85°C
温度范围: -25°C ~ +85°C
Insulation resistance: ≥1000MΩ
绝缘电阻: ≥1000MΩ
Contact resistance: ≤20mΩ
接触电阻: ≤20mΩ
Linetype: AWG#22 AWG#24 AWG#26 AWG#28

X9254 H IR - XX - N0

① ② ③ ④ ⑤

① Series No.

② Category: H-HSG

③ Welding Board Angle: I-HSG+Hardware R-Right Angle 90°

④ Row No.-Pin No.: XX-02P-30P

⑤ Material: N0-PA66 94V-0

Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B
2	2.54	5.20	10	22.86	25.52
3	5.08	7.72	11	25.40	28.06
4	7.62	10.28	12	27.94	30.60
5	10.16	12.82	30	73.66	76.32
6	12.70	15.36			
7	15.24	17.90			
8	17.78	20.44			
9	20.32	2.98			

X9254HIR-XX-N0	Nylon 66 UL 94V-0	Brass	Tim-Plated	X9254W
PART NO	Material	Material(Pin)	Finish(Terminal)	Wire Range

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWVN	DATE	VIEW:	PART NO.: 2.54mm IDC Style Connectors
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	X9254HIR-XX-N0
XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT SHEET REVISION
			1.0g 1/1 A0