

## Han 1HC-sti-s-M10 350A



Image is for illustration purposes only. Please refer to product description.

Part number	09 11 001 2655
Specification	Han 1HC-sti-s-M10 350A
HARTING eCatalogue	<a href="https://b2b.harting.com/09110012655">https://b2b.harting.com/09110012655</a>

### Identification

Category	Inserts
Series	Han <sup>®</sup> HC Modular
Identification	350

### Version

Termination method	Screw termination
Gender	Male
With wire protection	0
Details	Please ensure to hold up the contact with a wrench size 17 to apply the tightening torque

### Technical characteristics

Conductor cross-section	[120 mm <sup>2</sup> ]
Rated current	350 A
Rated voltage	2000 V
Rated impulse voltage	12 kV
Pollution degree	3
Insulation resistance	>10 <sup>10</sup> Ω
Contact resistance	≤0.2 mΩ
Tightening torque	[14 Nm]
Limiting temperature	[-40] ... [+125 °C]
Mating cycles	≥500



Pushing Performance

## Material properties

Material (insert)	Polycarbonate (PC) Polyamide (PA)
Colour (insert)	RAL 7032 (pebble grey)
Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate

## Specifications and approvals

Specifications	EN 60664-1 IEC 61984
Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076
CE	0

## Commercial data

Packaging size	1
Net weight	237 g
Country of origin	Romania
European customs tariff number	85359000
eCl@ss	27440205 Contact insert for industrial connectors