ALPHA & OMEGA SEMICONDUCTOR, INC.

August 2002

AO4415
P-Channel Enhancement Mode Field Effect Transistor


General Description


The AO4415 uses advanced trench technology to provide excellent $R_{DS(ON)}$, and ultra-low low gate charge. This device is suitable for use as a load switch or in PWM applications.

Features

V_{DS} (V) = -30V
I_D = -8 A
$R_{DS(ON)}$ < 26mΩ (V_{GS} = -20V)
$R_{DS(ON)}$ < 35mΩ (V_{GS} = -10V)

SOIC-8
Top View





Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	Maximum	Units
Drain-Source Voltage		V_{DS}	-30	V
Gate-Source Voltage		V_{GS}	±25	V
Continuous Drain Current [A]	T_A=25°C	I_D	-8	A
	T_A=70°C		-6.6	
Pulsed Drain Current [B]		I_{DM}	-40	
Power Dissipation [A]	T_A=25°C	P_D	3	W
	T_A=70°C		2.1	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	°C

Thermal Characteristics

Parameter		Symbol	Typ	Max	Units
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	24	40	°C/W
Maximum Junction-to-Ambient [A]	Steady-State		54	75	°C/W
Maximum Junction-to-Lead [C]	Steady-State	$R_{\theta JL}$	21	30	°C/W

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions		Min	Typ	Max	Units
STATIC PARAMETERS							
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=-250µA, V_{GS}=0V		-30			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=-24V, V_{GS}=0V				-1	µA
			T_J=55°C			-5	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}=±25V				±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS} I_D=-250µA		-1.7	-2.8	-3.5	V
$I_{D(ON)}$	On state drain current	V_{GS}=-10V, V_{DS}=-5V		40			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=-20V, I_D=-8A			21.5	26	mΩ
			T_J=125°C		29	35	
		V_{GS}=-10V, I_D=-8A			28.5	35	mΩ
		V_{GS}=-6V, I_D=-5A			41		mΩ
g_{FS}	Forward Transconductance	V_{DS}=-5V, I_D=-8A			11.5		S
V_{SD}	Diode Forward Voltage	I_S=-1A,V_{GS}=0V			-0.76	-1	V
I_S	Maximum Body-Diode Continuous Current					-4.2	A
DYNAMIC PARAMETERS							
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=-15V, f=1MHz			893		pF
C_{oss}	Output Capacitance				204		pF
C_{rss}	Reverse Transfer Capacitance				151		pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz			4		Ω
SWITCHING PARAMETERS							
Q_g(10V)	Total Gate Charge (10V)	V_{GS}=-10V, V_{DS}=-15V, I_D=-8A			16.6		nC
Q_{gs}	Gate Source Charge				3.2		nC
Q_{gd}	Gate Drain Charge				5.2		nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=-10V, V_{DS}=-15V, R_L=1.8Ω, R_{GEN}=3Ω			10.5		ns
t_r	Turn-On Rise Time				7.3		ns
$t_{D(off)}$	Turn-Off DelayTime				15.1		ns
t_f	Turn-Off Fall Time				8.6		ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=-8A, dI/dt=100A/µs			21		ns
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=-8A, dI/dt=100A/µs			10.7		nC

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A =25°C. The value in any a given application depends on the user's specific board design. The current rating is based on the t≤ 10s thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to lead $R_{\theta JL}$ and lead to ambient.

D. The static characteristics in Figures 1 to 6,12,14 are obtained using 80µs pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The SOA curve provides a single pulse rating.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)





Figure 11: Normalized Maximum Transient Thermal Impedance

ALPHA & OMEGA
SEMICONDUCTOR, INC.


SO-8 Package Data



SYMBOLS	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	1.45	1.50	1.55	0.057	0.059	0.061
A1	0.00	——	0.10	0.000	——	0.004
A2	——	1.45	——	——	0.057	——
b	0.33	——	0.51	0.013	——	0.020
c	0.19	——	0.25	0.007	——	0.010
D	4.80	——	5.00	0.189	——	0.197
E1	3.80	——	4.00	0.150	——	0.157
e	1.27 BSC			0.050 BSC		
E	5.80	——	6.20	0.228	——	0.244
h	0.25	——	0.50	0.010	——	0.020
L	0.40	——	1.27	0.016	——	0.050
aaa	——	——	0.10	——	——	0.004
θ	0°	——	8°	0°	——	8°

NOTE:
1. LEAD FINISH: 150 MICROINCHES (3.8 um) MIN. THICKNESS OF Tin/Lead (SOLDER) PLATED ON LEAD
2. TOLERANCE ±0.10 mm (4 mil) UNLESS OTHERWISE SPECIFIED
3. COPLANARITY : 0.10 mm
4. DIMENSION L IS MEASURED IN GAGE PLANE

PACKAGE MARKING DESCRIPTION




NOTE:
LOGO - AOS LOGO
4415 - PART NUMBER CODE.
F - FAB LOCATION
A - ASSEMBLY LOCATION
Y - YEAR CODE
W - WEEK CODE.
L C - ASSEMBLY LOT CODE

SOP-8 PART NO. CODE

PART NO.	CODE
AO4415	4415

RECOMMENDED LAND PATTERN




UNIT: mm

ALPHA & OMEGA
SEMICONDUCTOR, INC.

SO-8 Tape and Reel Data


SO-8 Carrier Tape



UNIT: MM

PACKAGE	A0	B0	K0	D0	D1	E	E1	E2	P0	P1	P2	T
SO-8 (12 mm)	6.40 ±0.10	5.20 ±0.10	2.10 ±0.10	1.60 ±0.10	1.50 +0.10	12.00 ±0.30	1.75 ±0.10	5.50 ±0.05	8.00 ±0.10	4.00 ±0.10	2.00 ±0.05	0.25 ±0.05

SO-8 Reel



UNIT: MM

TAPE SIZE	REEL SIZE	M	N	W	W1	H	K	S	G	R	V
12 mm	ø330	ø330.00 ±0.50	ø97.00 ±0.10	13.00 ±0.30	17.40 ±1.00	ø13.00 +0.50 -0.20	10.60	2.00 ±0.50	---	---	---

SO-8 Tape

Leader / Trailer & Orientation

