

PPC

POS-6511-PPC

Intel® Sandy Bridge processor to provide High Performance 15" POS Terminal

Features and Benefits:

- Intel® Sandy Bridge CPU series Processor High performance platform
- Ultra slim Panel PC
- 15" LCD display with ELO 5-wire resistive or ELO surface capacitive touch screen
- Flexible design for versatile applications
- VESA 100 Wall mounting standard
- Optional MSR & Smart card reader
- Ideal system to be floor-stand kiosk



Ultra slim



Protech Systems Co., Ltd.

No. 24, Lane 365, Yang Gong Street, Nei Hu District Taipei 114, Taiwan
 TEL: +886-2-8751-1111 FAX: +886-2-8751-1199
 E-mail: sales@protech.com.tw
 http://www.protech.com.tw

Protech Technologies Inc.

950 Fee Ana St, Suite B Placentia, CA 92870
 TEL: +1-714-996-7200 FAX: +1-714-996-7300
 Sales: sales@protech-usa.net
 http://www.protech-usa.net

Protech Japan Co., Ltd.

OSK Bldg, 6F, 6-25-14, Minami-ohi Shinagawa-ku, Tokyo, 140-0013
 TEL: +81-3-5753-8411 FAX: +81-3-3763-9282
 E-mail: sam@protech-j.com
 http://www.protech-j.com




ISO CERTIFIED
 9001 14001


POS-6511-PPC

Intel® Sandy Bridge processor to provide High Performance 15" POS Terminal


Front View



Side View



I/O View



Unit: mm

Specification

System

CPU Support	Intel® Celeron® Processor B810 (1.60 GHz) (up to Intel® Core i3-2330E 2.2GHz)
Memory	1GB DDR3 SO-DIMM (up to 4GB)
Core Logic	Mobile Intel® HM65 Express Chipset
Network	10/100/1000Base-T Fast Ethernet
Power Supply	72W~120W Power adapter
System Weight	5.5 kg
Dimension (W x H x D)	365 x 421.5 x 70 mm (14.37" x 16.59" x 2.76")
O.S. Support	Windows XP / 7, POSReady7, POSReady 2009
Mounting Type	Support VESA 100 standard

Storage

HDD	1 x 2.5" SATA HDD
SSD	over or equal 16GB
CF	1 x bootable Compact Flash slot for CF type I/II storage

I/O Ports

USB	4 x USB 2.0 port , 1xUSB 2.0 port on side 3 x DB-9 (COM 1/2/3), 1 x RJ45 (COM 4), +5/12V Selectable
Serial Ports	+5/12V Selectable
Parallel Port	1 x parallel port (SPP / EPP / ECP)
Keyboard & Mouse	1 x PS/2 port

LAN	1 x 10/100/1000 Mbps
Audio	1 x Line-out audio jack
VGA	1 x DB-15 VGA interface
Cash Drawer	1 x RJ11 port for 12V/24V Cash drawer

Display

LCD	15" TFT LCD
Max. Resolution	1024 x 768
Brightness	250 cd/m ²
Touch Screen	5-wire Analog resistive

Environment

EMC & Safety	CE, FCC
Operating Temp.	0 ~ 35° C
Storage Temp.	-20 ~ 60° C
Humidity	20 ~ 90%

Ordering Information

PA-6056RA-B0B	POS-6511-PPC, barebone, Black, ELO resistive touchscreen
PA-6056RZ-21A	DDR3 1GB Memory /2.5" HDD
PA-6055RZ-35B	Horizontal MSR Module (ID TECH PS2 interface)
PA-6053RZ-9EB	Vertical MSR module (ID TECH PS2 interface)
PA-6055RZ-61A	Embedded wireless module (802.11b/g)
PA-6055RZ-62B	vertical RFID module, ISO14443A(USB interface)

All of trademarks and brand names are the property of their owners. Trademark "Protech" is the property of Protech Systems Co., Ltd. All information contained in this document is subject to change without any prior notice. This catalog is copyrighted in May 2012.