Omnidirectional antenna - RAD-ISM-5000-ANT-PAR-18-N - 5606613

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



Flat panel antenna, 5 GHz, gain 18 dBi, connection N (female), IP55

Product description

Flat panel antenna, 5 GHz, gain 18 dBi, connection N (female), IP55

Why buy this product

- Directional wireless antennas with high gain for transmission over long distances

Key commercial data

Packing unit	1
Minimum order quantity	2
Catalog page	Page 129 (AX-2011)
GTIN	4 046356 479806
Weight per piece (including packing)	0.0 GRM
Weight per Piece (excluding packing)	1821.0 GRM
Country of origin	UNITED STATES

Technical data

General data

Frequency range	5 GHz
Frequency range	5.25 GHz ... 5.85 GHz
Horizontal beamwidth	18 °
Vertical beamwidth	18 °
Impedance	50 Ω
Gain	18 dBi
Connection method	N (female)
Degree of protection	IP55
Ambient temperature (operation)	-40 °C ... 70 °C
Width	152.4 mm
Height	152.4 mm

Omnidirectional antenna - RAD-ISM-5000-ANT-PAR-18-N - 5606613

Classifications

eclass

eClass 4.0	27250313
eClass 4.1	27250313
eClass 5.0	19070102
eClass 5.1	19070102
eClass 6.0	19070102

etim

ETIM 3.0	EC000416
ETIM 4.0	EC000416

unspsc

UNSPSC 6.01	43171611
UNSPSC 7.0901	43221706
UNSPSC 11	43171611
UNSPSC 12.01	43221706
UNSPSC 13.2	43221706

© Phoenix Contact 2012 - all rights reserved
http://www.phoenixcontact.com