



Material
 Insulator : PA6T Glass Fiber(U194-0)
 Terminal : Brass plated Tin
 Spring plate: SUS 301 plated Gold
 Cover : SPCC plated Ni

Specification
 Current Rating: 50mA DC 5V
 Insulation Resistance: 100MΩ Min. at 100V DC
 Dielectric Withstanding Voltage: AC 250V/ Min
 Operating Temperature: -20° C~+70° C
 Contact Resistance: 50mΩ Mix.

NO.	NAME	MATERIAL	NATIONALITY	QTY.	FINISHING
1	TERMINAL	Brass	China	1	Silver plating
2	CASE	PA66	China	1	Black
3	CONT ACT	Phosphor bronze	Korea	1	Contact side silver plating
4	BRACKET	SPCC-SD	China	1	CuSn plating
5	STEM	PA66 Chiro PC JAF	AN	1	H±9.5mm H>9.5mm

APPROVED:	DATE:	 深圳市灿科盟实业有限公司 CHINTW CHANKLEMENT INDUSTRY CO., LTD
CHECKED:	DATE:	
DRAWN:	DATE:	TITLE:
LYF	2008-11-24	轻触开关 646#5 带支架 侧按

TOLERANCE TABLE	
.0	±0.20
.00	±0.10
.000	±0.05

CLIENT P/N	C3025482
UNIT mm	SCALE free
FILE NO. K-KW02S01P-C000	SHEET 4/1
REV. A	REV. A
	GT01