

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0512382012](#)
Status: **Active**
Description: CRC™ Shielded Rectangular I/O Receptacle Housing for Female Terminal, Signal, 20 Circuits, Polarization Type A, Polarization Position B-2

Documents:
[Drawing \(PDF\)](#)
[Product Specification PS-51238-010 \(PDF\)](#)
[Product Specification PS-51238-018 \(PDF\)](#)
[RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA	LR19980
TUV	R72081037
UL	E29179

General

Product Family	I/O Connectors
Series	51238
Application	Panel-Mount, Wire-to-Wire
Component Type	Housing
Product Name	CRC™
Type	N/A

Physical

Boot Color	N/A
Circuits (Loaded)	N/A
Circuits (maximum)	20
Color - Resin	Black
Durability (mating cycles max)	100
Flammability	94V-0
Gender	Receptacle
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Metal	Stainless Steel
Material - Plating Mating	n/a
Material - Resin	Polyester
Number of Rows	5
Orientation	Vertical
PCB Locator	No
Packaging Type	Tray
Panel Mount	Front, Rear
Pitch - Mating Interface (in)	0.118 In
Pitch - Mating Interface (mm)	3.00 mm
Pitch - Term. Interface (in)	0.118 In
Pitch - Term. Interface (mm)	3.00 mm
Polarized to Mating Part	Yes
Polarized to PCB	N/A
Ports	1
Surface Mount Compatible (SMC)	N/A
Temperature Range - Operating	-40°C to +105°C
Termination Interface: Style	N/A
Waterproof / Dustproof	No

Electrical

Current - Maximum per Contact	1A, 2A, 3.5A, 3A
Shielded	No
Voltage - Maximum	250V AC (RMS)/DC



image - Reference only

Series

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Halogen-Free
Status
Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[51238Series](#)

Mates With
51234-200X plug housing|55836-200X plug assembly set

Use With
56377-200* receptacle shell|56120 and 56121 female terminal

Material Info

Reference - Drawing Numbers


Product Specification
Sales Drawing

PS-51238-010, PS-51238-018, RPS-51238-001
SD-51238-008

This document was generated on 04/12/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION



回路番号表示
CKT.No.IDENTIFICATION



電線挿入側
WIRE SIDE

19.7


シエル挿入方向キー
POLARIZATIONS KEY FOR SHELL



嵌合側
MATING SIDE

回路番号表示
CKT.No.IDENTIFICATION

シエル挿入方向キー
POLARIZATIONS KEY FOR SHELL



注記
NOTES



1. 材質
MATERIAL
①ハウジング: ガラス入りPBT樹脂
HOUSING: PBT G.F.
UL 94V-0 色: 黒
UL 94V-0 COLOR: BLACK
②スプリング: ステンレス鋼 t0.3
SPRING: STAINLESS STEEL t0.3
2. 適用端子: 56120-8*90, 56121-8*90
APPLICABLE CRIMP PIN: 56120-8*90, 56121-8*90
3. 適用リセプタクル シエル: 56377-20**
APPLICABLE RECEPTACLE SHELL: 56377-20**
4. 嵌合相手: 51234-200*
MEET WITH: 51234-200*

<誤嵌合防止キー(極性)タイプ> <POLARITY KEY TYPE>

51238-2011	51238-2012	51238-2013	51238-2014	51238-2015
STANDARD TYPE	A TYPE	B TYPE	C TYPE	D TYPE


C-4	D	51238-2015	51238-***	20
C-3	C	51238-2014		
B-3	B	51238-2013		
B-2	A	51238-2012		
—#—	STANDARD	51238-2011		
POLARITY POSITION (CIRCUIT No.)	POLARITY TYPE	MATERIAL No.	MODEL No.	CIRCUIT

EC NO. DRWN: CHK: APPR:	EC NO. DRWN: CHK: APPR:	EC NO. DRWN: CHK: APPR:	REVISED 01/10/04 EC NO. J2002-0786 DRWN: S.AKIYAMA CHK: J.MIYAZAWA APPR: Y.O.ITO	RELEASED 01/02/16 EC NO. JD2001-1040 DRWN: S.AKIYAMA CHK: J.MIYAZAWA APPR: H.IKESUGI	MATERIAL 材料 注記参照 SEE NOTES	GENERAL TOLERANCES: (UNLESS SPECIFIED) 一般公差		SCALE 2-1	DESIGN UNITS ☒ mm ☐ INCH	 THIRD ANGLE PROJECTION	☐ mm INCH ☐ INCH ☒ mm ONLY	REVISE ON CAD ONLY
						10 UNDER 未満	±0.2	DRAWN BY & DATE S. Akiyama 01/01/25	TITLE: COMPACT ROBOT CONN. (CRC) REC. SOCKET HS'G ASS'Y			
						10 OVER 以上 30 UNDER 未満	±0.25	CHECKED BY & DATE J. Miyazawa / Y. Ito				
						30 OVER 以上	±0.3	APPROVED BY & DATE H. Ikesugi				
WIRE RANGE 適用電線範囲	— # —	FINISH 仕上げ	— # —	ANGLE 角度	±3°	CAD FILE NAME 51238008.S01		MATERIAL NO. SEE CHART		DRAWING NO. SD-51238-008		SHEET NO. 1 OF 4
						THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.						SIZE B




嵌合図

CROSS-SECTION VIEW OF MATED CONNECTOR



EC NO. DRWN: CHK: APPR:	EC NO. DRWN: CHK: APPR:	EC NO. DRWN: CHK: APPR:	REVISED '01/10/04 EC NO. J2002-0786 DRWN: S.AKIYAMA CHK: J.MIYAZAWA APPR: Y.O.ITO	RELEASED '01/02/16 EC NO. JD2001-1040 DRWN: S.AKIYAMA CHK: J.MIYAZAWA APPR: H.IKESUGI	DESCRIPTION	MATERIAL 材料	注記参照 SEE NOTES	GENERAL TOLERANCES: (UNLESS SPECIFIED) 一般公差		SCALE 2-1	DESIGN UNITS ☒ mm ☐ INCH	THIRD ANGLE PROJECTION	☐ mm INCH	☐ INCH mm	☒ mm ONLY	REVISE ON CAD ONLY
						10 UNDER 未満		+0.2	DRAWN BY & DATE S. Akizawa 01/01/25		TITLE: COMPACT ROBOT CONN.(CRC) REC. SOCKET HS'G ASS'Y					
						10 OVER 30 UNDER 以上 未満		+0.25	CHECKED BY & DATE J. Miyazawa / Y.O.I							
						30 OVER 以上		+0.3	APPROVED BY & DATE H. Ikesugi		MOLEX INCORPORATED					
						WIRE RANGE 適用電線範囲		ANGLE 角度	+3°	CAD FILE NAME 51238008.S01		MATERIAL NO. SEE CHART	DRAWING NO. SD-51238-008		SHEET NO. 2 OF 4	
						INS. RANGE 被覆外径		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.						SIZE B		



嵌合図 (中継タイプ)

CROSS-SECTION VIEW OF MATED CONNECTOR
(WIRE TO WIRE TYPE)

EC NO. DRWN: CHK'g APPR:		EC NO. DRWN: CHK'g APPR:		EC NO. DRWN: CHK'g APPR:		REVISED 01/10/04 EC NO. J2002-0786 DRWN: S.AKIYAMA CHK'g: J.MIYAZAWA APPR: YO.ITO	0 EC NO. JD2001-1040 DRWN: S.AKIYAMA CHK'g: J.MIYAZAWA APPR: H.IKESUGI	DESCRIPTION MATERIAL 材料 FINISH 仕上げ WIRE RANGE 適用電線範囲 INS. RANGE 被覆外径	注記参照 SEE NOTES # # #	GENERAL TOLERANCES: (UNLESS SPECIFIED) 一般公差 10 UNDER 未満 10 OVER 以上 30 UNDER 未満 30 OVER 以上 ANGLE 角度	±0.2 ±0.25 ±0.3 ±3°	SCALE 2-1 DRAWN BY & DATE S. Akiyama / 01/25 CHECKED BY & DATE J. Miyazawa / Y. Ito APPROVED BY & DATE H. Ikesugi CAD FILE NAME 51238008.S03	DESIGN UNITS mm INCH THIRD ANGLE PROJECTION TITLE: COMPACT ROBOT CONN. (CRC) REC. SOCKET HS'G ASS'Y MOLEX INCORPORATED	DIMENSIONS: mm INCH SHT REV REVISE ON CAD ONLY	MATERIAL NO. SEE CHART DRAWING NO. SD-51238-008 SHEET NO. 3 OF 4 SIZE B
-----------------------------------	--	-----------------------------------	--	-----------------------------------	--	---	--	--	----------------------------------	---	------------------------------	---	---	---	--

DWG. NO.
SD-51233-008

F


D

A

C

B

DO NOT SCALE DRAWING



嵌合図 (中継タイプ)
CROSS-SECTION VIEW OF MATED CONNECTOR
(WIRE TO WIRE TYPE)

EC NO. DRWN: CHK: APPR:			EC NO. DRWN: CHK: APPR:			EC NO. DRWN: CHK: APPR:			REVISED 01/10/04 EC NO. J2002-0786 DRWN: S.AKIYAMA CHK: J.MIYAZAWA APPR: YO.ITO			RELEASED 01/02/16 EC NO. JD2001-1040 DRWN: S.AKIYAMA CHK: J.MIYAZAWA APPR: HIKESUGI			DESCRIPTION			MATERIAL 材料 注記参照 SEE NOTES			GENERAL TOLERANCES: (UNLESS SPECIFIED) 一般公差			SCALE 2-1			DESIGN UNITS ☒ mm ☐ INCH			 THIRD ANGLE PROJECTION			☐ mm INCH ☐ INCH ☒ mm ONLY			SHEET NO. REVISE ON CAD ONLY		
															FINISH 仕上り			10 UNDER 未満			±0.2			DRAWN BY & DATE S. Akiyama 01/01/25			TITLE: COMPACT ROBOT CONN. (CRC) REC. SOCKET HS'G ASS'Y											
															10 OVER 30 UNDER 以上 未満			±0.25			CHECKED BY & DATE J. Miyazawa / Y. Ito																	
															30 OVER 以上			±0.3			APPROVED BY & DATE H. Ikesugi			MOLEX INCORPORATED														
															WIRE RANGE 適用電線範囲			ANGLE 角度			±3°			CAD FILE NAME 51238008.S04			MATERIAL NO. SEE CHART			DRAWING NO. SD-51238-008			SHEET NO. 4 OF 4					
															INS. RANGE 被覆外径									THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.												SIZE B		

51238008.S04