

HWS30A-3/HD



Sales Region	Worldwide
Series	HWS-A/HD
Status	Production
Feature	
Option	Harsh environment
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics

Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 370V
Efficiency	77% Typ.
Rated Output Voltage[DC]	3.3V
Output Voltage Range[DC]	2.97 to 3.96V
Maximum Output Current	6A
Maximum Output Power	20W

Cases Shape & Size

Case shape	Unit
Width(W)	26.5mm Nom.
Height(H)	82mm Nom.
Depth(D)	95mm Nom.
Weight	200g Typ.

Other

Operating Temp. Range	-10 to 71°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1 CSA C22.2 No.60950-1 EN60950-1
Safety Standard(Conformed)	Den-an Appendix 8 at 100VAC only
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.