



SPECIFICATIONS
 Current rating: 2A AC/DC
 Voltage rating: 250V AC/DC
 Contact resistance: 20mΩ max.
 Withstand voltage: 800V AC/min
 Insulation resistance: 1000MΩ/min.
 Temperature range: -25°C~+85°C
 Applicable PC board thickness: 0.031"~0.063"(0.8-1.6)

Material:
 Post: Brass, Tin plated
 Base: PA46, UL94V-2

Poles	Part No.	Dimension mm		
		A	B	C
2	2001SMTN-2P	8.0	4.7	2.0
3	2001SMTN-3P	10.0	6.7	4.0
4	2001SMTN-4P	12.0	8.7	6.0
5	2001SMTN-5P	14.0	10.7	8.0
6	2001SMTN-6P	16.0	12.7	10.0
7	2001SMTN-7P	18.0	14.7	12.0
8	2001SMTN-8P	20.0	16.7	14.0
9	2001SMTN-9P	22.0	18.7	16.0
10	2001SMTN-10P	24.0	20.7	18.0
11	2001SMTN-11P	26.0	22.7	20.0
12	2001SMTN-12P	28.0	24.7	22.0
13	2001SMTN-13P	30.0	26.7	24.0
14	2001SMTN-14P	32.0	28.7	26.0
15	2001SMTN-15P	34.0	30.7	28.0

APPROVED:	DATE:	TITLE:	
CHECKED:	DATE:	2001SMT-XP (立贴)	
TOLERANCE TABLE		CLIENT P/N	SCALE
.0	±0.20	/	free
.00	±0.10	UNIT mm	REV. A
.000	±0.05	FILE NO. Chantw-2001-0015	
DRAWN: LYF	DATE: 2008-05-28		

APPROVED: **Chantw CHANKLEMENT INDUSTRY CO., LTD**
 DATE: 2008-05-28
 TITLE: 2001SMT-XP (立贴)

CLIENT P/N / SCALE free

UNIT mm FILE NO. Chantw-2001-0015 REV. A