

Sales Region	Worldwide (except Japan)
Series	DPP
Model	DPP30
Status	 Production
Feature	
Options	
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	
Brand	TDK-Lambda



Electrical Characteristics	
Input	Single-phase
Input Voltage Range[AC]	85 to 264Vac
Input Voltage Range[DC]	
Efficiency	82% Typ.
Rated Output Voltage[DC]	12Vdc
Output Voltage Range[DC]	9.9 to 12.1Vdc
Maximum Output Current	2.5A
Maximum Output Power	30W

Package Type & Size	
Package / Mounting	DIN rail
Industry Standard Size	
Width(W)	45mm Nom. (1.77in Nom.)
Height(H)	75mm Nom. (2.95in Nom.)
Depth(D)	91mm Nom. (3.58in Nom.)
Weight	260g Typ. (0.6lbs Typ.)

Other	
Operating Temp. Range	-10 to 71°C
Cooling	Convection
Safety Standard(Certified)	EN60950-1
	UL60950-1
	UL508
	UL1310 Class 2
Safety Standard(Conformed)	

Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.
---------	---

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.