

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [34708-3082](#)
Status: **Active**
Overview: Stac64™ Single, Multi-Pocket and Hybrid Header System
Description: Stac64™ 3 Bay Right Angle Headers, 28 Circuits, Bay A 12 Circuit Signal Header, Polarization C, Brown; Bay B 8 Circuit Signal Header, Polarization B, Gray; Bay C 8 Circuit Signal Header, Polarization B, Tray

Documents:


3D Model	Application Specification AS-34729-020 (PDF)
Drawing (PDF)	RoHS Certificate of Compliance (PDF)
Product Specification PS-31372-100 (PDF)	Product Literature (PDF)
Product Specification PS-34729-020 (PDF)	

General

Product Family	PCB Headers
Series	34708
Application	Power, Wire-to-Board
Comments	Bay A 12 Circuits Stac64™ Right Angle Signal Header, Polarization C. Bay B 8 Circuits Stac64™ Right Angle Signal Header, Polarization B. Bay C 8 Circuits Stac64™ Right Angle Signal Header, Polarization B
Overview	<u>Stac64™ Single, Multi-Pocket and Hybrid Header System</u>
Product Literature Order No	987650-4561
Product Name	Stac64™
UPC	884982148291

Physical

Breakaway	No
Circuits (Loaded)	28
Circuits (maximum)	28
Color - Resin	Black, Brown, Gray
Durability (mating cycles max)	10
First Mate / Last Break	No
Glow-Wire Compliant	No
Guide to Mating Part	No
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Metal	Copper Alloy
Material - Plating Mating	Nickel
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	16.498/g
Number of Rows	2
Orientation	Right Angle
PC Tail Length	3.36mm
PCB Locator	Yes
PCB Retention	None
PCB Thickness - Recommended	1.57mm
Packaging Type	Tray
Pitch - Mating Interface	2.54mm
Pitch - Termination Interface	2.54mm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Shrouded	Yes
Stackable	No



EU RoHS

ELV and RoHS Compliant
REACH SVHC Contains SVHC: No
Low-Halogen Status Low-Halogen

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[34708Series](#)

Mates With

[31408](#) USCAR 2.54mm (.100") Pitch Receptacle, [31372](#) 5.25mm (.206") Pitch Hybrid Receptacle Assembly, [34729](#) 2.54mm (.100") Pitch Stac64™ Right Angle Receptacle

Surface Mount Compatible (SMC)	N/A
Temperature Range - Operating	-40°C to +100°C
Termination Interface: Style	Through Hole

Electrical

Current - Maximum per Contact	Contact Molex
Voltage - Maximum	500V

Material Info**Reference - Drawing Numbers**

Application Specification	AS-34729-020
Product Specification	PS-31372-100, PS-34729-020
Sales Drawing	SD-34708-300

This document was generated on 09/16/2014

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION