

14 NIM-S26C

Intel® XL710 PCI-Express 10G SFP+ 4 Ports Module



Specifications

Main Specification	
Form Factor	10G Fiber Module
Main Chipset	Intel® XL710 Ethernet Controller x 1
Bypass	—
Host Interface	PCI-Express [x8]
LAN Port	SFP+ 10 GbE Connector x 4
Indicator	LED x 4 for Active/Link
Qualification	CE/FCC Class A
Operation Temp.	32°F ~ 104°F (0°C ~ 40°C)
Dimension	5.71" x 3.03" (145mm x 77mm)

Features

- PCI-Express Host Interfaces
- 10G SFP+ Fiber Port x 4



Network Appliance Options

- **FWS-7810/7811**
1U Rackmount Network Appliance, Intel® C226 with 1 Network Interface Modules
- **FWS-7820**
1U Rackmount Network Appliance, Intel® C236 with 4 Network Interface Modules
- **FWS-7520**
1U Rackmount Network Appliance, Intel® Broadwell DE with 3 of NIM appliance

Ordering Information

- **NIM-S26C-A10-T40-0001**
LAN Module, Intel® XL710, 10 GbE SFP+ x 4, FWS-7520, Rev. A.1.0
- **NIM-S26C-A10-T40-0002**
LAN Module, Intel® XL710, 10 GbE SFP+ x 4, FWS-7820, Rev. A.1.0
- **NIM-S26C-A10-T40-0003**
LAN Module, Intel® XL710, 10 GbE SFP+ x 4, FWS-7810/7811, Rev. A.1.0