NCS2220A

Low Voltage Comparator

The NCS2220A is an industry first sub−one volt, low power dual comparator. This device consumes only 7.5 μA per Comparator of supply current. It is guaranteed to operate at a low voltage of 0.85 V which allows it to be used in systems that require less than 1.0 V and is fully operational up to 6.0 V which makes it convenient for use in both 3.0 V and 5.0 V systems. Additional features include no output phase inversion with overdriven inputs, internal hysteresis, which allows for clean output switching, and rail−to−rail input and output performance. The NCS2220A is available in the tiny UDFN 1.6 X 1.6 package.

Features


- Operating Voltage of 0.85 V to 6.0 V
- Rail−to−Rail Input/Output Performance
- Low Supply Current of 7.5 μA per Comparator Typ
- No Phase Inversion with Overdriven Input Signals
- Internal Hysteresis
- Propagation Delay of 0.5 μs
- This is a Pb−Free Device

Typical Applications


- Single Cell NiCd/NiMH Battery Powered Applications
- Cellular Telephones
- Alarm and Security Systems
- Personal Digital Assistants

ON Semiconductor®

http://onsemi.com




UDFN8 1.6 X 1.6
MU SUFFIX
CASE 517AC



CZ = Specific Device Code
M = Date Code
▪ = Pb−Free Package
(Note: Microdot may be in either location)

PIN CONNECTIONS



Top View

ORDERING INFORMATION

Device	Package	Shipping†
NCS2220AMUT1G	Complementary UDFN 1.6 X 1.6	3000/ Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2006

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Supply Voltage Range (V_{CC} to V_{EE})	V_S	6.0	V
Non−inverting/Inverting Input to V_{EE}	−	−0.2 to (V_{CC} + 0.2)	V
Operating Junction Temperature	T_J	150	°C
Operating Ambient Temperature	T_A	−40 to +105	°C
Storage Temperature Range	T_{stg}	−65 to +150	°C
Output Short Circuit Duration Time (Note 1)	t_S	Indefinite	s
ESD Tolerance (Note 2) NCS2220A Human Body Model Machine Model	−	 2000 200	V
Thermal Resistance, Junction−to−Ambient UDFN	$R_{\theta JA}$	 350	°C/W

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. The maximum package power dissipation limit must not be exceeded.

$$P_D = \frac{T_{J(max)} - T_A}{R_{\theta JA}}$$

2. ESD data available upon request.

ELECTRICAL CHARACTERISTICS (For all values V_{CC} = 0.85 V to 6.0 V, V_{EE} = 0 V, T_A = 25°C, unless otherwise noted.) (Note 3)

Characteristics	Symbol	Min	Typ	Max	Unit
Input Hysteresis T_A = 25°C	V_{HYS}	2.0	4.5	20	mV
Input Offset Voltage	V_{IO}				mV
V_{CC} = 0.85 V					
T_A = 25°C		−10	0.5	+10	
T_A = −40°C to 105°C		−12	−	+12	
V_{CC} = 3.0 V					
T_A = 25°C		−6.0	0.5	+6.0	
T_A = −40°C to 105°C		−8.0	−	+8.0	
V_{CC} = 6.0 V					
T_A = 25°C		−5.0	0.5	+5.0	
T_A = −40°C to 105°C		−7.0	−	+7.0	
Common Mode Voltage Range	V_{CM}	−	V_{EE} to V_{CC}	−	V
Output Short−Circuit Sourcing or Sinking	I_{SC}	−	60	−	mA
Common Mode Rejection Ratio V_{CM} = V_{CC}	CMRR	53	70	−	dB
Input Bias Current	I_{IB}	−	1.0	−	pA
Power Supply Rejection Ratio ΔV_S = 2.575 V	PSRR	45	80	−	dB
Supply Current per Comparator	I_{CC}				μA
V_{CC} = 0.85 V					
T_A = 25°C		−	7.5	15	
T_A = −40°C to 105°C			−	17	
V_{CC} = 3.0 V					
T_A = 25°C		−	8.0	15	
T_A = −40°C to 105°C			−	17	
V_{CC} = 6.0 V					
T_A = 25°C		−	9.0	15	
T_A = −40°C to 105°C			−	17	
Output Voltage High	V_{OH}				V
V_{CC} = 0.85 V, I_{source} = 0.5 mA					
T_A = 25°C		V_{CC} − 0.25	V_{CC} − 0.12	−	
T_A = −40°C to 105°C		V_{CC} − 0.275	−		
V_{CC} = 3.0 V, I_{source} = 3.0 mA					
T_A = 25°C		V_{CC} − 0.3	V_{CC} − 0.12	−	
T_A = −40°C to 105°C		V_{CC} − 0.35	−		
V_{CC} = 6.0 V, I_{source} = 5.0 mA					
T_A = 25°C		V_{CC} − 0.3	V_{CC} − 0.17	−	
T_A = −40°C to 105°C		V_{CC} − 0.35	−		
Output Voltage Low	V_{OL}				V
V_{CC} = 0.85 V, I_{sink} = 0.5 mA					
T_A = 25°C		−	V_{EE} + 0.10	V_{EE} + 0.25	
T_A = −40°C to 105°C			−	V_{EE} + 0.275	
V_{CC} = 3.0 V, I_{sink} = 3.0 mA					
T_A = 25°C		−	V_{EE} + 0.12	V_{EE} + 0.3	
T_A = −40°C to 105°C			−	V_{EE} + 0.35	
V_{CC} = 6.0 V, I_{sink} = 5.0 mA					
T_A = 25°C		−	V_{EE} + 0.12	V_{EE} + 0.3	
T_A = −40°C to 105°C			−	V_{EE} + 0.35	
Propagation Delay 20 mV Overdrive, C_L = 15 pF					μs
	t_{PHL}	−	0.5	−	
	t_{PLH}	−	0.5	−	
Output Fall Time V_{CC} = 6.0 V, C_L = 50 pF (Note 4)	t_{FALL}	−	20	−	ns
Output Rise Time V_{CC} = 6.0 V, C_L = 50 pF (Note 4)	t_{RISE}	−	16	−	ns

3. The limits over the extended temperature range are guaranteed by design only.
4. Input signal: 1 kHz, squarewave signal with 10 ns edge rate.




Figure 1. NCS2220A Supply Current versus Temperature/Comparator




Figure 2. NCS2220A Supply Current versus Output Transition Frequency/Comparator




Figure 3. NCS2220A Supply Current versus Supply Voltage/Comparator




Figure 4. NCS2220A Output Voltage High State versus Output Source Current




Figure 5. NCS2220A Output Voltage Low State versus Output Sink Current




Figure 6. NCS2220A Output Voltage Low State versus Temperature




Figure 7. NCS2220A Output Voltage High State versus Temperature




Figure 8. NCS2220A Propagation Delay versus Temperature




Figure 9. NCS2220A Output Response Time versus Supply Voltage




Figure 10. NCS2220A Propagation Delay versus Input Overdrive




Figure 11. NCS2220A Propagation Delay versus Input Overdrive




Figure 12. NCS2220A Powerup Delay




Figure 13. NCS2220A Input Common Mode Voltage Range versus Supply Voltage

OPERATING DESCRIPTION

The NCS2220A is an industry first sub−one volt, low power comparator. This device is designed for rail−to−rail input and output performance. This device consumes only 10 μA/Comparator of supply current while achieving a typical propagation delay of 1.1 μs at a 20 mV input overdrive. Figures 10 and 11 show propagation delay with various input overdrives. This comparator is guaranteed to operate at a low voltage of 0.85 V up to 6.0 V. This is accomplished by the use of a modified analog CMOS process that implements depletion MOSFET devices. The common−mode input voltage range extends 0.1 V beyond the upper and lower rail without phase inversion or other adverse effects. This device has a typical internal hysteresis of ±8.0 mV. This allows for greater noise immunity and clean output switching.

Output Stage

The NCS2220A has a complementary P and N Channel output stage that has capability of driving a rail−to−rail output swing with a load ranging up to 5.0 mA. It is designed such that shoot−through current is minimized while switching. This feature eliminates the need for bypass capacitors under most circumstances.






Figure 14. NCS2220A Complementary Output Configuration



The oscillation frequency can be programmed as follows:


$$f = \frac{1}{T} = \frac{1}{2.2\ R_X C_X}$$

Figure 15. Schmitt Trigger Oscillator



The resistor divider R_1 and R_2 can be used to set the magnitude of the input pulse. The pulse width is set by adjusting C_1 and R_3.

Figure 16. One−Shot Multivibrator



This circuit converts 5 V logic to 3 V logic. Using the NCS2220A allows for full 5 V logic swing without creating overvoltage on the 3 V logic input.

Figure 17. Logic Level Translator







Figure 18. Zero−Crossing Detector

PACKAGE DIMENSIONS

UDFN8, 1.6x1.6, 0.4P
CASE 517AC−01
ISSUE A








NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.25 AND 0.30 mm FROM TERMINAL.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.
5. EXPOSED PADS CONNECTED TO DIE FLAG. USED AS TEST CONTACTS.

	MILLIMETERS		
DIM	MIN	NOM	MAX
A	0.45	0.50	0.55
A1	0.00	0.03	0.05
A3		0.127 REF	
b	0.15	0.20	0.25
D		1.60 BSC	
D2	0.70	0.80	0.90
E		1.60 BSC	
E2	0.40	0.50	0.60
e		0.40 BSC	
K	0.20	−−−	−−−
L	0.20	0.30	0.40

SOLDERING FOOTPRINT*



*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5773−3850

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

NCS2220A/D