

1A, 400V N-CHANNEL POWER MOSFET



SOT-223



TO-251

■ DESCRIPTION


The UTC **1N40A** is an N-channel mode power MOSFET using UTC' s advanced technology to provide customers with planar stripe and DMOS technology. This technology is specialized in allowing a minimum on-state resistance and superior switching performance. It also can withstand high energy pulse in the avalanche and commutation mode.

The UTC **1N40A** is universally applied in electronic lamp ballast based on half bridge topology and high efficient switched mode power supply.

■ FEATURES

* High switching speed
* $R_{DS(ON)}$ < 6.8Ω @ V_{GS} = 10V, I_D = 0.5A
* 100% avalanche tested

■ SYMBOL



■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
-	1N40AG-AA3-R	SOT-223	G	D	S	Tape Reel
1N40AL-TM3-T	1N40AG-TM3-T	TO-251	G	D	S	Tube



Note: Pin Assignment: G: Gate D: Drain S: Source

1N40AG-TA3-R

(1)Packing Type	(1) T: Tubel, R: Tape Reel
(2)Package Type	(2) AA3: SOT-223, TM3: TO-251
(3)Green Package	(3) L: Lead Free, G: Halogen Free and Lead Free

Copyright © 2015 Unisonic Technologies Co., Ltd

■ MARKING

SOT-223	TO-251
	

■ ABSOLUTE MAXIMUM RATINGS (T_C=25°C, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DSS}	400	V
Gate-Source Voltage		V_{GSS}	±30	V
Drain Current	Continuous (T_C=25°C)	I_D	1	A
	Pulsed (Note 2)	I_{DM}	4	A
Avalanche Energy	Single Pulsed (Note 3)	E_{AS}	40	mJ
Peak Diode Recovery dv/dt (Note 4)		dv/dt	4.5	V/ns
Power Dissipation	SOT-223	P_D	1	W
	TO-251		25	W
Derate above 25°C	SOT-223	P_D	125	W/°C
	TO-251		0.2	W/°C
Junction Temperature		T_J	+150	°C
Storage Temperature		T_{STG}	-55~+150	°C

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.
2. Repetitive Rating: Pulse width limited by maximum junction temperature
3. L = 80mH, I_{AS} = 1A, V_{DD} = 50V, R_G = 25Ω, Starting T_J = 25°C
4. I_{SD} ≤ 1.8A, di/dt ≤ 200A/μs, V_{DD} ≤ BV_{DSS}, Starting T_J = 25°C

■ THERMAL DATA

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient	SOT-223	θ_{JA}	150	°C/W
	TO-251		110	°C/W
Junction to Case	SOT-223	θ_{JC}	125	°C/W
	TO-251		5	°C/W


■ ELECTRICAL CHARACTERISTICS (T_C=25°C, unless otherwise noted)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV_{DSS}	I_D=250μA, V_{GS}=0V	400			V
Breakdown Voltage Temperature Coefficient		$\triangle BV_{DSS}/\triangle T_J$	Reference to 25°C, I_D=250μA		0.4		V/°C
Drain-Source Leakage Current		I_{DSS}	V_{DS}=400V, V_{GS}=0V			1	μA
Gate- Source Leakage Current	Forward	I_{GSS}	V_{GS}=+30V, V_{DS}=0V			+100	nA
	Reverse		V_{GS}=-30V, V_{DS}=0V			-100	nA
ON CHARACTERISTICS							
Gate Threshold Voltage		$V_{GS(TH)}$	V_{DS}=V_{GS}, I_D=250μA	2.0		4.0	V
Static Drain-Source On-State Resistance		$R_{DS(ON)}$	V_{GS}=10V, I_D=0.5A		4.0	6.8	Ω
DYNAMIC PARAMETERS							
Input Capacitance		C_{ISS}	V_{GS}=0V, V_{DS}=25V, f=1.0MHz		125	150	pF
Output Capacitance		C_{OSS}			20	30	pF
Reverse Transfer Capacitance		C_{RSS}			17	28	pF
SWITCHING PARAMETERS							
Total Gate Charge		Q_G	V_{GS}=10V, V_{DS}=50V, I_D=1.3A (Note 1, 2)		10	15	nC
Gate to Source Charge		Q_{GS}			3.22		nC
Gate to Drain Charge		Q_{GD}			0.8		nC
Turn-ON Delay Time		$t_{D(ON)}$	V_{DD}=30V, I_D=0.5A, R_G=25Ω (Note 1, 2)		33	40	ns
Rise Time		t_R			20	35	ns
Turn-OFF Delay Time		$t_{D(OFF)}$			58	78	ns
Fall-Time		t_F			17	30	ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS							
Maximum Body-Diode Continuous Current		I_S				1.0	A
Maximum Body-Diode Pulsed Current		I_{SM}				4.0	A
Drain-Source Diode Forward Voltage		V_{SD}	I_S=1A, V_{GS}=0V			1.5	V


Notes: 1. Pulse Test: Pulse width ≤ 300μs, Duty cycle ≤ 2%
2. Essentially independent of operating temperature

■ TEST CIRCUITS AND WAVEFORMS

Resistive Switching Test Circuit



Resistive Switching Waveforms



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.