



## Pluggable PCB Connectors

### GST 865 VO/ 7

Male Header Vertical, Pin Spacing: 5.08 mm, 7 pole, Voltage Rating: 250 V, Current Rating: 12 A, Connection Type: Solder

#### Order Info

<b>Reference Number (ref. no.)</b>	378007
<b>Applications</b>	Lighting, Electrical Appliances, Electronics
<b>PU</b>	200

#### Type

<b>Type</b>	Male Header Vertical
<b>Number of poles</b>	7 pole
<b>Colour</b>	blue
<b>Connection Type</b>	Solder
<b>Protection Against Incorrect Plugging</b>	yes

#### Technical Data

<b>Voltage Rating</b>	250 V
<b>Current Rating</b>	12 A
<b>Insulating Material</b>	PBT
<b>Contact Material</b>	Brass
<b>Flammability Rating</b>	V-0
<b>max. Ambient Temperature Operation</b>	60 °C
<b>Type of Conductor Solid</b>	yes
<b>Type of Conductor Flexible</b>	yes
<b>Type of Conductor Stranded</b>	yes
<b>Pin Spacing</b>	5.08 mm
<b>Approbation EN61984</b>	GSK860_GST860_GSK865_GST865_EN61984_20060302_20110512
<b>Approbation UL</b>	GSK760_GSK860_GSK864_GSK865_UL_E63492_1-11_Description_v
<b>Approbation CSA</b>	GSK_GST_Printklemmen_Serie_20160404_CSA_70070893_Certificat