NX3L2267

Low-ohmic dual single-pole double-throw analog switch

Rev. 5 — 18 June 2012 Product data sheet

1. General description

The NX3L2267 is a dual low-ohmic single-pole double-throw analog switch suitable for use as an analog or digital 2:1 multiplexer/demultiplexer. Each switch has a digital select input (nS), two independent inputs/outputs (nY0 and nY1) and a common input/output (nZ).

Schmitt trigger action at the digital inputs makes the circuit tolerant to slower input rise and fall times. Low threshold digital inputs allows this device to be driven by 1.8 V logic levels in 3.3 V applications without significant increase in supply current I_{CC}. This makes it possible for the NX3L2267 to switch 4.3 V signals with a 1.8 V digital controller, eliminating the need for logic level translation. The NX3L2267 allows signals with amplitude up to V_{CC} to be transmitted from nZ to nY0 or nY1, or from nY0 or nY1 to nZ. Its low ON resistance (0.5 Ω) and flatness (0.13 Ω) ensures minimal attenuation and distortion of transmitted signals.

2. Features and benefits

- Wide supply voltage range from 1.4 V to 4.3 V
- Very low ON resistance (peak):
  - 1.65 Ω (typical) at V_{CC} = 1.4 V
  - 0.95 Ω (typical) at V_{CC} = 1.65 V
  - 0.55 Ω (typical) at V_{CC} = 2.3 V
  - 0.50 Ω (typical) at V_{CC} = 2.7 V
  - 0.50 Ω (typical) at V_{CC} = 4.3 V
- Break-before-make switching
- High noise immunity
- ESD protection:
  - HBM JESD22-A114F Class 3A exceeds 7500 V
  - MM JESD22-A115-A exceeds 200 V
  - CDM AEC-Q100-011 revision B exceeds 1000 V
  - IEC61000-4-2 contact discharge exceeds 6000 V for switch ports
- CMOS low-power consumption
- Latch-up performance exceeds 100 mA per JESD 78B Class II Level A
- 1.8 V control logic at V_{CC} = 3.6 V
- Control input accepts voltages above supply voltage
- Very low supply current, even when input is below V_{CC}
- High current handling capability (350 mA continuous current under 3.3 V supply)
- Specified from –40 °C to +85 °C and from –40 °C to +125 °C

3. Applications

- Cell phone
- PDA
- Portable media player

4. Ordering information

Table 1. Ordering information

Type number	Package			
	Temperature range	Name	Description	Version
NX3L2267GM	−40 °C to +125 °C	XQFN10	plastic extremely thin quad flatpackage; no leads; 10 terminals; body 2 × 1.55 × 0.5 mm	SOT1049-3
NX3L2267GU	−40 °C to +125 °C	XQFN10	plastic, extremely thin quad flat package; no leads; 10 terminals; body 1.40 × 1.80 × 0.50 mm	SOT1160-1

5. Marking

Table 2. Marking

Type number	Marking code
NX3L2267GM	M67
NX3L2267GU	M7

6. Functional diagram




Fig 1. Logic symbol




Fig 2. Logic diagram (one switch)

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2012. All rights reserved.

7. Pinning information

7.1 Pinning




Fig 3. Pin configuration SOT1049-3 (XQFN10)




Fig 4. Pin configuration SOT1160-1 (XQFN10)

7.2 Pin description

Table 3. Pin description

Symbol	Pin		Description
	SOT1049-3	SOT1160-1	
1Y0	1	10	independent input or output
1Y1	2	1	independent input or output
2Y0	3	2	independent input or output
2Y1	4	3	independent input or output
GND	5	4	ground (0 V)
2Z	6	5	common output or input
2S	7	6	select input
1S	8	7	select input
1Z	9	8	common output or input
V_{CC}	10	9	supply voltage

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2012. All rights reserved.

8. Functional description

Table 4. Function table[1]

Input nS	Channel on
L	nY0 = nZ
H	nY1 = nZ

[1] H = HIGH voltage level; L = LOW voltage level.

9. Limiting values

Table 5. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND (ground = 0 V).

Symbol	Parameter	Conditions		Min	Max	Unit
V_{CC}	supply voltage			–0.5	+4.6	V
V_I	input voltage	select input nS	[1]	–0.5	+4.6	V
V_{SW}	switch voltage		[2]	–0.5	V_{CC} + 0.5	V
I_{IK}	input clamping current	V_I < –0.5 V		–50	-	mA
I_{SK}	switch clamping current	V_I < –0.5 V or V_I > V_{CC} + 0.5 V		-	±50	mA
I_{SW}	switch current	V_{SW} > –0.5 V or V_{SW} < V_{CC} + 0.5 V; source or sink current		-	±350	mA
		V_{SW} > –0.5 V or V_{SW} < V_{CC} + 0.5 V; pulsed at 1 ms duration, < 10 % duty cycle; peak current		-	±500	mA
T_{stg}	storage temperature			–65	+150	°C
P_{tot}	total power dissipation	T_{amb} = –40 °C to +125 °C	[3][4]	-	250	mW

[1] The minimum input voltage rating may be exceeded if the input current rating is observed.

[2] The minimum and maximum switch voltage ratings may be exceeded if the switch clamping current rating is observed but may not exceed 4.6 V.

[3] For XQFN10 (SOT1049-3) package: above 132 °C the value of P_{tot} derates linearly with 14.1 mW/K.

[4] For XQFN10 (SOT1160-1) package: above 128 °C the value of P_{tot} derates linearly with 11.5 mW/K.

10. Recommended operating conditions

Table 6. Recommended operating conditions

Symbol	Parameter	Conditions		Min	Max	Unit
V_{CC}	supply voltage			1.4	4.3	V
V_I	input voltage	select input nS		0	4.3	V
V_{SW}	switch voltage	switch input nY0 or nY1	[1]	0	V_{CC}	V
T_{amb}	ambient temperature			–40	+125	°C
$\Delta t/\Delta V$	input transition rise and fall rate	V_{CC} = 1.4 V to 4.3 V	[2]	-	200	ns/V

[1] To avoid sinking GND current from terminal nZ when switch current flows in terminal nYn, the voltage drop across the bidirectional switch must not exceed 0.4 V. If the switch current flows into terminal nZ, no GND current will flow from terminal nYn. In this case, there is no limit for the voltage drop across the switch.

[2] Applies to select input nS signal levels.

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2012. All rights reserved.

11. Static characteristics

Table 7. Static characteristics


At recommended operating conditions; voltages are referenced to GND (ground 0 V).

Symbol	Parameter	Conditions	T_{amb} = 25 °C			T_{amb} = –40 °C to +125 °C			Unit
			Min	Typ	Max	Min	Max (85 °C)	Max (125 °C)	
V_{IH}	HIGH-level input voltage	V_{CC} = 1.4 V to 1.6 V	0.9	-	-	0.9	-	-	V
		V_{CC} = 1.65 V to 1.95 V	0.9	-	-	0.9	-	-	V
		V_{CC} = 2.3 V to 2.7 V	1.1	-	-	1.1	-	-	V
		V_{CC} = 2.7 V to 3.6 V	1.3	-	-	1.3	-	-	V
		V_{CC} = 3.6 V to 4.3 V	1.4	-	-	1.4	-	-	V
V_{IL}	LOW-level input voltage	V_{CC} = 1.4 V to 1.6 V	-	-	0.3	-	0.3	0.3	V
		V_{CC} = 1.65 V to 1.95 V	-	-	0.4	-	0.4	0.3	V
		V_{CC} = 2.3 V to 2.7 V	-	-	0.5	-	0.5	0.4	V
		V_{CC} = 2.7 V to 3.6 V	-	-	0.5	-	0.5	0.5	V
		V_{CC} = 3.6 V to 4.3 V	-	-	0.6	-	0.6	0.6	V
I_I	input leakage current	select input nS; V_I = GND to 4.3 V; V_{CC} = 1.4 V to 4.3 V	-	-	-	-	±0.5	±1	µA
$I_{S(OFF)}$	OFF-state leakage current	nYn port; see Figure 5							
		V_{CC} = 1.4 V to 3.6 V	-	-	±5	-	±10	±100	nA
		V_{CC} = 3.6 V to 4.3 V	-	-	±10	-	±50	±200	nA
$I_{S(ON)}$	ON-state leakage current	nZ port; see Figure 6							
		V_{CC} = 1.4 V to 3.6 V	-	-	±5	-	±20	±200	nA
		V_{CC} = 3.6 V to 4.3 V	-	-	±10	-	±50	±400	nA
I_{CC}	supply current	V_I = V_{CC} or GND; V_{SW} = GND or V_{CC}							
		V_{CC} = 3.6 V	-	-	100	-	300	3000	nA
		V_{CC} = 4.3 V	-	-	150	-	500	5000	nA
ΔI_{CC}	additional supply current	V_{SW} = GND or V_{CC}							
		V_I = 2.6 V; V_{CC} = 4.3 V	-	2.0	4.0	-	7	7	µA
		V_I = 2.6 V; V_{CC} = 3.6 V	-	0.35	0.7	-	1	1	µA
		V_I = 1.8 V; V_{CC} = 4.3 V	-	7.0	10.0	-	15	15	µA
		V_I = 1.8 V; V_{CC} = 3.6 V	-	2.5	4.0	-	5	5	µA
		V_I = 1.8 V; V_{CC} = 2.5 V	-	50	200	-	300	500	nA
C_I	input capacitance		-	1.0	-	-	-	-	pF
$C_{S(OFF)}$	OFF-state capacitance	port nYn	-	35	-	-	-	-	pF
$C_{S(ON)}$	ON-state capacitance	port nYn	-	135	-	-	-	-	pF

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2012. All rights reserved.


11.1 Test circuits



switch	nS
1	V_{IH}
2	V_{IL}

V_I = 0.3 V or V_{CC} − 0.3 V; V_O = V_{CC} − 0.3 V or 0.3 V.

Fig 5. Test circuit for measuring OFF-state leakage current



switch	nS
1	V_{IH}
2	V_{IL}

V_I = 0.3 V or V_{CC} − 0.3 V; V_O = V_{CC} − 0.3 V or 0.3 V.

Fig 6. Test circuit for measuring ON-state leakage current

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2012. All rights reserved.

11.2 ON resistance

Table 8. ON resistance

At recommended operating conditions; voltages are referenced to GND (ground = 0 V); for graphs see Figure 8 to Figure 14.

Symbol	Parameter	Conditions	–40 °C to +85 °C			–40 °C to +125 °C		Unit
			Min	Typ[1]	Max	Min	Max	
$R_{ON(peak)}$	ON resistance (peak)	port nYn; V_I = GND to V_{CC}; I_{SW} = 100 mA; see Figure 7						
		V_{CC} = 1.4 V	-	1.65	3.7	-	4.1	Ω
		V_{CC} = 1.65 V	-	0.95	1.6	-	1.7	Ω
		V_{CC} = 2.3 V	-	0.55	0.8	-	0.9	Ω
		V_{CC} = 2.7 V	-	0.50	0.75	-	0.9	Ω
		V_{CC} = 4.3 V	-	0.50	0.75	-	0.9	Ω
ΔR_{ON}	ON resistance mismatch between channels	V_I = GND to V_{CC}; I_{SW} = 100 mA [2]						
		V_{CC} = 1.4 V	-	0.20	0.35	-	0.35	Ω
		V_{CC} = 1.65 V	-	0.20	0.25	-	0.30	Ω
		V_{CC} = 2.3 V	-	0.09	0.13	-	0.15	Ω
		V_{CC} = 2.7 V	-	0.09	0.125	-	0.15	Ω
		V_{CC} = 4.3 V	-	0.09	0.125	-	0.15	Ω
$R_{ON(flat)}$	ON resistance (flatness)	port nYn; V_I = GND to V_{CC}; I_{SW} = 100 mA [3]						
		V_{CC} = 1.4 V	-	1.05	3.35	-	3.65	Ω
		V_{CC} = 1.65 V	-	0.55	1.25	-	1.35	Ω
		V_{CC} = 2.3 V	-	0.20	0.35	-	0.40	Ω
		V_{CC} = 2.7 V	-	0.18	0.35	-	0.40	Ω
		V_{CC} = 4.3 V	-	0.23	0.40	-	0.45	Ω

[1] Typical values are measured at T_{amb} = 25 °C.


[2] Measured at identical V_{CC}, temperature and input voltage.

[3] Flatness is defined as the difference between the maximum and minimum value of ON resistance measured at identical V_{CC} and temperature.

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2012. All rights reserved.


11.3 ON resistance test circuit and graphs



switch	nS
1	V_{IL}
2	V_{IH}

$R_{ON} = V_{SW} / I_{SW}$.

Fig 7. Test circuit for measuring ON resistance




(1) V_{CC} = 1.5 V.
(2) V_{CC} = 1.8 V.
(3) V_{CC} = 2.5 V.
(4) V_{CC} = 2.7 V.
(5) V_{CC} = 3.3 V.
(6) V_{CC} = 4.3 V.

Measured at T_{amb} = 25 °C.

Fig 8. Typical ON resistance as a function of input voltage (Yn port)


All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2012. All rights reserved.




(1) T_{amb} = 125 °C.
(2) T_{amb} = 85 °C.
(3) T_{amb} = 25 °C.
(4) T_{amb} = −40 °C.

Fig 9. ON resistance as a function of input voltage; V_{CC} = 1.5 V (nYn port)




(1) T_{amb} = 125 °C.
(2) T_{amb} = 85 °C.
(3) T_{amb} = 25 °C.
(4) T_{amb} = −40 °C.

Fig 10. ON resistance as a function of input voltage; V_{CC} = 1.8 V (nYn port)



(1) T_{amb} = 125 °C.
(2) T_{amb} = 85 °C.
(3) T_{amb} = 25 °C.
(4) T_{amb} = −40 °C.

Fig 11. ON resistance as a function of input voltage; V_{CC} = 2.5 V (nYn port)




(1) T_{amb} = 125 °C.
(2) T_{amb} = 85 °C.
(3) T_{amb} = 25 °C.
(4) T_{amb} = −40 °C.

Fig 12. ON resistance as a function of input voltage; V_{CC} = 2.7 V (nYn port)


All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2012. All rights reserved.



(1) T_{amb} = 125 °C.
(2) T_{amb} = 85 °C.
(3) T_{amb} = 25 °C.
(4) T_{amb} = –40 °C.

Fig 13. ON resistance as a function of input voltage; V_{CC} = 3.3 V



(1) T_{amb} = 125 °C.
(2) T_{amb} = 85 °C.
(3) T_{amb} = 25 °C.
(4) T_{amb} = –40 °C.

Fig 14. ON resistance as a function of input voltage; V_{CC} = 4.3 V

12. Dynamic characteristics

Table 9. Dynamic characteristics

At recommended operating conditions; voltages are referenced to GND (ground = 0 V); for load circuit see Figure 17.

Symbol	Parameter	Conditions	T_{amb} = 25 °C			T_{amb} = –40 °C to +125 °C			Unit
			Min	Typ[1]	Max	Min	Max (85 °C)	Max (125 °C)	
t_{en}	enable time	nS to nZ or nYn; see Figure 15							
		V_{CC} = 1.4 V to 1.6 V	-	50	90	-	120	120	ns
		V_{CC} = 1.65 V to 1.95 V	-	36	70	-	80	90	ns
		V_{CC} = 2.3 V to 2.7 V	-	24	45	-	50	55	ns
		V_{CC} = 2.7 V to 3.6 V	-	22	40	-	45	50	ns
		V_{CC} = 3.6 V to 4.3 V	-	22	40	-	45	50	ns
t_{dis}	disable time	nS to nZ or nYn; see Figure 15							
		V_{CC} = 1.4 V to 1.6 V	-	32	70	-	80	90	ns
		V_{CC} = 1.65 V to 1.95 V	-	20	55	-	60	65	ns
		V_{CC} = 2.3 V to 2.7 V	-	12	25	-	30	35	ns
		V_{CC} = 2.7 V to 3.6 V	-	10	20	-	25	30	ns
		V_{CC} = 3.6 V to 4.3 V	-	10	20	-	25	30	ns

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2012. All rights reserved.

Table 9. Dynamic characteristics *...continued*


At recommended operating conditions; voltages are referenced to GND (ground = 0 V); for load circuit see Figure 17.

Symbol	Parameter	Conditions	T_{amb} = 25 °C			T_{amb} = –40 °C to +125 °C			Unit
			Min	Typ[1]	Max	Min	Max (85 °C)	Max (125 °C)	
t_{b-m}	break-before-make time	see Figure 16 [2]							
		V_{CC} = 1.4 V to 1.6 V	-	19	-	9	-	-	ns
		V_{CC} = 1.65 V to 1.95 V	-	17	-	7	-	-	ns
		V_{CC} = 2.3 V to 2.7 V	-	13	-	4	-	-	ns
		V_{CC} = 2.7 V to 3.6 V	-	10	-	3	-	-	ns
		V_{CC} = 3.6 V to 4.3 V	-	10	-	2	-	-	ns

[1] Typical values are measured at T_{amb} = 25 °C and V_{CC} = 1.5 V, 1.8 V, 2.5 V, 3.3 V and 4.3 V respectively.

[2] Break-before-make guaranteed by design.

12.1 Waveform and test circuits



Measurement points are given in Table 10.

Logic level: V_{OH} is typical output voltage level that occurs with the output load.


Fig 15. Enable and disable times

Table 10. Measurement points


Supply voltage	Input	Output
V_{CC}	V_M	V_X
1.4 V to 4.3 V	$0.5V_{CC}$	$0.9V_{OH}$

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2012. All rights reserved.




a. Test circuit.



b. Input and output measurement points

Fig 16. Test circuit for measuring break-before-make timing



Test data is given in Table 11.

Definitions test circuit:

R_L = Load resistance.

C_L = Load capacitance including jig and probe capacitance.

V_{EXT} = External voltage for measuring switching times.

Fig 17. Test circuit for measuring switching times

Table 11. Test data

Supply voltage	Input		Load	
V_{CC}	V_I	t_r, t_f	C_L	R_L
1.4 V to 4.3 V	V_{CC}	≤ 2.5 ns	35 pF	50 Ω

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2012. All rights reserved.

12.2 Additional dynamic characteristics

Table 12. Additional dynamic characteristics

At recommended operating conditions; voltages are referenced to GND (ground = 0 V); V_I = GND or V_{CC} (unless otherwise specified); $t_r = t_f \leq 2.5$ ns.


Symbol	Parameter	Conditions		T_{amb} = 25 °C			Unit
				Min	Typ	Max	
THD	total harmonic distortion	f_i = 20 Hz to 20 kHz; R_L = 32 Ω; see Figure 18	[1]				
		V_{CC} = 1.4 V; V_I = 1 V (p-p)		-	0.15	-	%
		V_{CC} = 1.65 V; V_I = 1.2 V (p-p)		-	0.10	-	%
		V_{CC} = 2.3 V; V_I = 1.5 V (p-p)		-	0.02	-	%
		V_{CC} = 2.7 V; V_I = 2 V (p-p)		-	0.02	-	%
		V_{CC} = 4.3 V; V_I = 2 V (p-p)		-	0.02	-	%
		V_{CC} = 3.0 V; V_I = 1 V (p-p); R_L = 600 Ω		-	0.01	-	%
$f_{(-3dB)}$	−3 dB frequency response	R_L = 50 Ω; see Figure 19	[1]				
		port nYn; V_{CC} = 1.4 V to 4.3 V		-	60	-	MHz
α_{iso}	isolation (OFF-state)	f_i = 100 kHz; R_L = 50 Ω; see Figure 20	[1]				
		V_{CC} = 1.4 V to 4.3 V		-	−90	-	dB
V_{ct}	crosstalk voltage	between digital inputs and switch; f_i = 1 MHz; C_L = 50 pF; R_L = 50 Ω; see Figure 21					
		V_{CC} = 1.4 V to 3.6 V		-	0.21	-	V
		V_{CC} = 3.6 V to 4.3 V		-	0.30	-	V
Xtalk	crosstalk	between switches; f_i = 100 kHz; R_L = 50 Ω; see Figure 22	[1]				
		V_{CC} = 1.4 V to 4.3 V		-	−90	-	dB
Q_{inj}	charge injection	f_i = 1 MHz; C_L = 0.1 nF; R_L = 1 MΩ; V_{gen} = 0 V; R_{gen} = 0 Ω; see Figure 23					
		V_{CC} = 1.5 V		-	4	-	pC
		V_{CC} = 1.8 V		-	6	-	pC
		V_{CC} = 2.5 V		-	16	-	pC
		V_{CC} = 3.3 V		-	24	-	pC
		V_{CC} = 4.3 V		-	37	-	pC

[1] f_i is biased at $0.5V_{CC}$.

All information provided in this document is subject to legal disclaimers.


© NXP B.V. 2012. All rights reserved.

12.3 Test circuits



switch	nS
1	V_{IL}
2	V_{IH}


Fig 18. Test circuit for measuring total harmonic distortion



switch	nS
1	V_{IL}
2	V_{IH}

Adjust f_i voltage to obtain 0 dBm level at output. Increase f_i frequency until dB meter reads −3 dB.

Fig 19. Test circuit for measuring the frequency response when channel is in ON-state




switch	nS
1	V_{IH}
2	V_{IL}

Adjust f_i voltage to obtain 0 dBm level at input.


Fig 20. Test circuit for measuring isolation (OFF-state)

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2012. All rights reserved.




a. Test circuit



b. Input and output pulse definitions

Fig 21. Test circuit for measuring crosstalk voltage between digital inputs and switch




$20 \log_{10} (V_{O2} / V_{O1})$ or $20 \log_{10} (V_{O1} / V_{O2})$.


Fig 22. Test circuit for measuring crosstalk between switches

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2012. All rights reserved.



a. Test circuit.



b. Input and output pulse definitions

Definition: $Q_{inj} = \Delta V_O \times C_L$.

ΔV_O = output voltage variation.

R_{gen} = generator resistance.

V_{gen} = generator voltage.


Fig 23. Test circuit for measuring charge injection

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2012. All rights reserved.

13. Package outline

XQFN10: plastic, extremely thin quad flat package; no leads; 10 terminals; body 1.55 x 2.00 x 0.50 mm **SOT1049-3**



Dimensions

Unit(1)		A	A1	b	b1	c	D	E	e	e1	L	L1	v	w	y	y1
mm	max	0.5	0.05	0.25	0.33		1.65	2.1			0.48	0.40				
	nom			0.20	0.28	0.127	1.55	2.0	0.5	1.5	0.43	0.35	0.1	0.05	0.05	0.05
	min		0.00	0.15	0.23		1.45	1.9			0.38	0.30				

Note
1. Plastic or metal protrusions of 0.075 mm maximum per side are not included.

sot1049-3_po


Outline version	References				European projection	Issue date
	IEC	JEDEC	JEITA			
SOT1049-3	- - -	MO255	- - -			~~10-12-06~~ 11-03-30

Fig 24. Package outline SOT1049-3 (XQFN10)

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2012. All rights reserved.

XQFN10: plastic, extremely thin quad flat package; no leads; 10 terminals; body 1.40 x 1.80 x 0.50 mm **SOT1160-1**



Dimensions

Unit[1]		A	A_1	A_3	b	D	E	e	e_1	e_2	L	L_1	v	w	y	y_1
	max	0.5	0.05		0.25	1.5	1.9				0.45	0.55				
mm	nom			0.127	0.20	1.4	1.8	0.4	0.8	0.4	0.40	0.50	0.1	0.05	0.05	0.05
	min		0.00		0.15	1.3	1.7				0.35	0.45				

Note

1. Plastic or metal protrusions of 0.075 mm maximum per side are not included.

sot1160-1_po

Outline version	References			European projection	Issue date
	IEC	JEDEC	JEITA		
SOT1160-1	- - -	- - -	- - -		~~09-12-28~~ 09-12-29

Fig 25. Package outline SOT1160-1 (XQFN10)

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2012. All rights reserved.

14. Abbreviations

Table 13. Abbreviations

Acronym	Description
CDM	Charged Device Model
CMOS	Complementary Metal-Oxide Semiconductor
ESD	ElectroStatic Discharge
HBM	Human Body Model
MM	Machine Model

15. Revision history

Table 14. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
NX3L2267 v.5	20120618	Product data sheet	-	NX3L2267 v.4
Modifications:	• Package outline drawing SOT1049-2 changed to SOT1049-3 (Figure 24).			
NX3L2267 v.4	20111108	Product data sheet	-	NX3L2267 v.3
Modifications:	• Legal pages updated.			
NX3L2267 v.3	20101223	Product data sheet	-	NX3L2267 v.2
NX3L2267 v.2	20100713	Product data sheet	-	NX3L2267 v.1
NX3L2267 v.1	20091109	Product data sheet	-	-

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2012. All rights reserved.

16. Legal information

16.1 Data sheet status

Document status[1][2]	Product status[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL http://www.nxp.com.

16.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between NXP Semiconductors and its customer, unless NXP Semiconductors and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the NXP Semiconductors product is deemed to offer functions and qualities beyond those described in the Product data sheet.

16.3 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. NXP Semiconductors takes no responsibility for the content in this document if provided by an information source outside of NXP Semiconductors.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of NXP Semiconductors.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors and its suppliers accept no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at http://www.nxp.com/profile/terms, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. NXP Semiconductors hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of NXP Semiconductors products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2012. All rights reserved.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Non-automotive qualified products — Unless this data sheet expressly states that this specific NXP Semiconductors product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. NXP Semiconductors accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without NXP Semiconductors' warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond NXP Semiconductors' specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies NXP Semiconductors for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond NXP Semiconductors' standard warranty and NXP Semiconductors' product specifications.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

16.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

17. Contact information

For more information, please visit: **http://www.nxp.com**

For sales office addresses, please send an email to: **salesaddresses@nxp.com**

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2012. All rights reserved.

18. Contents

1	**General description**	**1**
2	**Features and benefits**	**1**
3	**Applications**	**2**
4	**Ordering information**	**2**
5	**Marking**	**2**
6	**Functional diagram**	**2**
7	**Pinning information**	**3**
7.1	Pinning	3
7.2	Pin description	3
8	**Functional description**	**4**
9	**Limiting values**	**4**
10	**Recommended operating conditions**	**4**
11	**Static characteristics**	**5**
11.1	Test circuits	6
11.2	ON resistance	7
11.3	ON resistance test circuit and graphs	8
12	**Dynamic characteristics**	**10**
12.1	Waveform and test circuits	11
12.2	Additional dynamic characteristics	13
12.3	Test circuits	14
13	**Package outline**	**17**
14	**Abbreviations**	**19**
15	**Revision history**	**19**
16	**Legal information**	**20**
16.1	Data sheet status	20
16.2	Definitions	20
16.3	Disclaimers	20
16.4	Trademarks	21
17	**Contact information**	**21**
18	**Contents**	**22**

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© NXP B.V. 2012. **All rights reserved.**

For more information, please visit: http://www.nxp.com
For sales office addresses, please send an email to: salesaddresses@nxp.com

Date of release: 18 June 2012
Document identifier: NX3L2267