


REVISIONS			
REV.	DESCRIPTION	ECN NO.	DATE
01	FIRST RELEASE FOR RFQ#A2014-13459	N/A	06/10/14
02	UPDATE DESIGN AS CUSTOMER'S REQUEST	EE16116	10/10/14
03	UPDATE DESIGN AS CUSTOMER'S REQUEST	EE16187	11/14/14

PAGE 4 IS FOR INTERNAL ONLY

PART NUMBER		PART DESCRIPTION		TITLE			
835-01300F		RoHS compliant per EU Directive 2011/65/EU		PXFM, ETD29, 550uH, TH, 14Pin			
<p align="center"><u>WARNING !</u></p> <p>ALL SHEETS OF THIS DOCUMENT ARE CONTROLLED DOCUMENTATION AND ARE NOT TO BE RELEASED OUTSIDE OF E&E OR ITS SUB-CONTRACTORS WITHOUT AUTHORIZATION.</p>		UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCH/mm.		E & E Magnetic Products Ltd.			
		APPROVALS		DATE			
		DRAWN BY		B.XU		11/14/14	
		PROJ. ENG		S.HONG		11/14/14	
		APPROVED BY		J.YANG		11/14/14	
Q.A.		D.LUO		11/14/14			
TOLERANCE ARE:				DRAWING NO./MODEL			
INCH .XXX ± .005		mm .XX ± .13		835-01300F			
ANGLE X.X ± 0.3				REV			
.XX ± .02		.X ± .5		03			
X ± 1				SCALE			
				DO NOT SCALE			
				PAGE 1 OF 4			



MECHANICAL OUTLINE



E & E Magnetic Products Ltd.

DRAWING NO./MODEL

835-01300F

REV

03

SCALE

DO NOT SCALE

PAGE

2


OF

4

1. Dimension are specified in $\frac{\text{inches}}{\text{mm}}$ with higher precedence in mm.
2. Unless otherwise specified, all tolerance are $\pm \frac{.010}{0.25}$.
3. "(DATE)" includes at least the manufacturing date code (in YYWW format) plus manufacturing site code.
4. Remove PIN 4.


ELECTRICAL SPECIFICATION @25°C:

PARAMETERS	UNIT	LIMIT
Turns Ratio(1-2):(2-3):(7-6):(10-13)	-	1 : 1 : 0.267 : 0.7 ± 2%
Polarity	-	As per schematic
Ls(1-3)@1kHz, 1Vrms	uH	550 ± 5%
Hipot(1-2-3-6-7):(10-13)@5mA,1 Min.	Vrms	3000



SCHEMATIC

- Operating temperature range: -40°C to +125°C. The part temperature (ambient temperature + temperature rise) should not exceed the upper limit of the operating temperature under worst case operating conditions. Circuit design, component placement, PWB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.
- The transformer is designed to meet reinforced insulation.(Creepage distance between Pri.-Sec.=6.4mm)

 E & E Magnetic Products Ltd.		
DRAWING NO./MODEL		REV
835-01300F		03
SCALE	PAGE	OF
DO NOT SCALE	3	4