


Sales Region	Worldwide (except Japan)
Series	DPX
Model	DPX30
Status	 Production
Option	
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	



Electrical Characteristics

Nominal Input Voltage[DC]	24Vdc
Input Voltage Range[DC]	10 to 40Vdc
Efficiency	84% Typ.
Rated Output Voltage[DC]	12Vdc
Output Voltage Range[DC]	Fixed
Output Current Range	0 to 2.5A
Maximum Ripple Noise	100mV
Maximum Output Power	30W
Withstanding Voltage1	Input - Case: 1600DC: 1min.
Withstanding Voltage2	Input - Output: 1600DC: 1min.
Withstanding Voltage3	Output - Case: 1600DC: 1min.

Package Type & Size

Package / Mounting	DIN rail
Width(W)	125mm Nom. (4.92in Nom.)
Height(H)	57.6mm Nom. (2.27in Nom.)
Depth(D)	24.5mm Nom. (0.96in Nom.)
Weight	170g Typ.
Industry Standard Size	
Terminal Style	Block terminal

Other

Operating Temp. Range	-40 to 90°C
Isolation	Isolated
Feature	MIL-STD-810F EN55022 Class B
Safety Standard(Certified)	IEC60950-1 EN60950-1 UL60950-1

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

Safety Standard(Conformed)

Remarks

This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.