

RoHS Compliant Product
A suffix of "-C" specifies halogen & lead-free

FEATURES

- Small reverse transfer capacitance : $C_{re} = 0.55\text{pF}$ (typ.)
- Low noise figure : $NF=2\text{dB}$ (typ.) ($f=100\text{MHz}$)


CLASSIFICATION OF h_{FE}

| Product-Rank | 2SC4215-R | 2SC4215-O | 2SC4215-Y |
|--------------|-----------|-----------|-----------|
| Range | 40~80 | 70~140 | 100~200 |
| Marking | QR | QO | QY |


PACKAGE INFORMATION

| Package | MPQ | LeaderSize |
|---------|-----|------------|
| SOT-323 | 3K | 7' inch |

SOT-323



| REF. | Millimeter | | REF. | Millimeter | |
|------|------------|------|------|------------|------|
| | Min. | Max. | | Min. | Max. |
| A | 1.80 | 2.20 | G | 0.100 REF. | |
| B | 1.80 | 2.45 | H | 0.525 REF. | |
| C | 1.15 | 1.35 | J | 0.08 | 0.25 |
| D | 0.80 | 1.10 | K | - | - |
| E | 1.20 | 1.40 | L | 0.650 TYP. | |
| F | 0.20 | 0.40 | | | |









ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise specified)

| Parameter | Symbol | Rating | Unit |
|--------------------------------|----------------|--------------|------------------|
| Collector-Base Voltage | V_{CBO} | 40 | V |
| Collector-Emitter Voltage | V_{CEO} | 30 | V |
| Emitter-Base Voltage | V_{EBO} | 4 | V |
| Collector Current | I_C | 20 | mA |
| Collector Power Dissipation | P_C | 100 | mW |
| Junction & Storage temperature | T_J, T_{STG} | 150, -55~150 | $^\circ\text{C}$ |

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise specified)

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Test Condition |
|-------------------------------------|---------------|------|------|------|---------------|-------------------------------------------------------|
| Collector-Base Breakdown Voltage | $V_{(BR)CBO}$ | 40 | - | - | V | $I_C=100\mu\text{A}, I_E=0$ |
| Collector-Emitter Breakdown Voltage | $V_{(BR)CEO}$ | 30 | - | - | V | $I_C=1\text{mA}, I_B=0$ |
| Emitter-Base Breakdown Voltage | $V_{(BR)EBO}$ | 4 | - | - | V | $I_E=100\mu\text{A}, I_C=0$ |
| Collector Cut-off Current | I_{CBO} | - | - | 0.1 | μA | $V_{CB}=40\text{V}, I_E=0$ |
| Emitter Cut-off Current | I_{EBO} | - | - | 0.5 | μA | $V_{EB}=4\text{V}, I_C=0$ |
| DC Current Gain | h_{FE} | 40 | - | 200 | | $V_{CE}=6\text{V}, I_C=1\text{mA}$ |
| Collector-Base Time Constant | $C_c.f_{bb}$ | - | - | 25 | ps | $V_{CE}=6\text{V}, I_C=1\text{mA}, f=30\text{MHz}$ |
| Transition Frequency | f_T | 260 | 550 | - | MHz | $V_{CE}=6\text{V}, I_C=1\text{mA}$ |
| Reverse Transfer Capacitance | C_{re} | - | 0.55 | - | pF | $V_{CB}=10\text{V}, f=1\text{MHz}$ |
| Noise Figure | NF | - | 2 | 5 | dB | $V_{CC}=6\text{V}, I_C=1\text{mA}, f=100\text{MHz}$, |
| Power Gain | G_{pe} | 17 | 23 | - | dB | |

CHARACTERISTIC CURVES



CHARACTERISTIC CURVES

