


TC74VCX125FT

LOW-VOLTAGE QUAD BUS BUFFER WITH 3.6V TOLERANT INPUTS AND OUTPUTS

The TC74VCX125FT is a high performance CMOS QUAD BUS BUFFER. Designed for use in 1.8, 2.5 or 3.3 Volt systems, it achieves high speed operation while maintaining the CMOS low power dissipation. It is also designed with over voltage tolerant inputs and outputs up to 3.6V.

This device requires the 3-state control input $\overline{OE}$ to be set high to place the output into the high impedance state.

All inputs are equipped with protection circuits against static discharge.



TSSOP14-P-0044-0.65

Weight : 0.06g (Typ.)

FEATURES


- Low Voltage Operation: $V_{CC} = 1.8 \sim 3.6V$
- High Speed Operation : $t_{pd} = TBD$ (max.) at $V_{CC} = 3.0 \sim 3.6V$
 $t_{pd} = TBD$ (max.) at $V_{CC} = 2.3 \sim 2.7V$
 $t_{pd} = TBD$ (max.) at $V_{CC} = 1.8V$
- 3.6V Tolerant inputs and outputs.
- Output Current : $I_{OH}/I_{OL} = \pm 24mA$ (min.) at $V_{CC} = 3.0V$
 $I_{OH}/I_{OL} = \pm 18mA$ (min.) at $V_{CC} = 2.3V$
 $I_{OH}/I_{OL} = \pm 6mA$ (min.) at $V_{CC} = 1.8V$
- Latch-up Performance : $\pm 300mA$
- ESD Performance : Human Body Model $> \pm 2000V$
Machine Model $> \pm 200V$
- Package : TSSOP
(Thin Shrink Small Outline Package)
- Power Down Protection is provided on all inputs and outputs.
- Supports live insertion / withdrawal (Note 1)

(Note 1) To ensure the high-impedance state during power up or power down, $\overline{OE}$ should be tied to V_{CC} through a pullup resistor; the minimum value of the resistor is determined by the current-sourcing capability of the driver.


980508EBA1

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The products described in this document are subject to foreign exchange and foreign trade laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

PIN ASSIGNMENT



IEC LOGIC SYMBOL



TRUTH TABLE

INPUTS		OUTPUTS
$\overline{OE}$	A	Y
H	X	Z
L	L	L
L	H	H

X : Don't Care

Z : High Impedance

PRELIMINARY

MAXIMUM RATINGS

PARAMETER	SYMBOL	RATING	UNIT
Power Supply Voltage	V_{CC}	-0.5~4.6	V
DC Input Voltage	V_{IN}	-0.5~4.6	V
DC Output Voltage	V_{OUT}	-0.5~4.6 (Note 1)	V
		-0.5~ $V_{CC} + 0.5$ (Note 2)	
Input Diode Current	I_{IK}	-50	mA
Output Diode Current	I_{OK}	±50 (Note 3)	mA
DC Output Current	I_{OUT}	±50	mA
Power Dissipation	P_D	180	mW
DC V_{CC} /Ground Current	I_{CC}/I_{GND}	±100	mA
Storage Temperature	T_{stg}	-65~150	°C

(Note 1) Off-State

(Note 2) High or Low State. I_{OUT} absolute maximum rating must be observed.(Note 3) $V_{OUT} < GND$, $V_{OUT} > V_{CC}$

RECOMMENDED OPERATING RANGE

PARAMETER	SYMBOL	RATING	UNIT
Supply Voltage	V_{CC}	1.8~3.6	V
		1.2~3.6 (Note 4)	
Input Voltage	V_{IN}	-0.3~3.6	V
Output Voltage	V_{OUT}	0~3.6 (Note 5)	V
		0~ V_{CC} (Note 6)	
Output Current	I_{OH}/I_{OL}	± 24 (Note 7)	mA
		± 18 (Note 8)	
		± 6 (Note 9)	
Operating Temperature	T_{opr}	-40~85	°C
Input Rise And Fall Time	dt/dv	0~10 (Note 10)	ns/V

(Note 4) Data Retention Only

(Note 5) Off-State

(Note 6) High or Low State

(Note 7) $V_{CC} = 3.0 \sim 3.6V$ (Note 8) $V_{CC} = 2.3 \sim 2.7V$ (Note 9) $V_{CC} = 1.8V$ (Note 10) $V_{IN} = 0.8 \sim 2.0V$, $V_{CC} = 3.0V$

PRELIMINARY

ELECTRICAL CHARACTERISTICS

DC characteristics ($T_a = -40 \sim 85^\circ\text{C}$, $2.7V < V_{CC} \leq 3.6V$)

PARAMETER		SYMBOL	TEST CONDITION		V _{CC} (V)	MIN.	MAX.	UNIT
Input Voltage	“H” Level	V _{IH}			2.7~3.6	2.0	—	V
	“L” Level	V _{IL}			2.7~3.6	—	0.8	
Output Voltage	“H” Level	V _{OH}	V _{IN} = V _{IH} or V _{IL}	I _{OH} = - 100μA	2.7~3.6	V _{CC} - 0.2	—	V
				I _{OH} = - 12mA	2.7	2.2	—	
				I _{OH} = - 18mA	3.0	2.4	—	
				I _{OH} = - 24mA	3.0	2.2	—	
	“L” Level	V _{OL}	V _{IN} = V _{IH} or V _{IL}	I _{OL} = 100μA	2.7~3.6	—	0.2	
				I _{OL} = 12mA	2.7	—	0.4	
				I _{OL} = 18mA	3.0	—	0.4	
				I _{OL} = 24mA	3.0	—	0.55	
Input Leakage Current		I _{IN}	V _{IN} = 0~3.6V	2.7~3.6	—	± 5.0	μA	
3-State Output Off-State Current		I _{OZ}	V _{IN} = V _{IH} or V _{IL} V _{OUT} = 0~3.6V	2.7~3.6	—	± 10.0	μA	
Power Off Leakage Current		I _{OFF}	V _{IN} , V _{OUT} = 0~3.6V	0	—	10.0	μA	
Quiescent Supply Current		I _{CC}	V _{IN} = V _{CC} or GND	2.7~3.6	—	20.0	μA	
			V _{CC} ≦ (V _{IN} , V _{OUT}) ≦ 3.6V	2.7~3.6	—	± 20.0		
Increase In I _{CC} Per Input		ΔI _{CC}	V _{IH} = V _{CC} - 0.6V	2.7~3.6	—	750	μA	

ELECTRICAL CHARACTERISTICS

DC characteristics ($T_a = -40 \sim 85^\circ\text{C}$, $2.3\text{V} \leq V_{CC} \leq 2.7\text{V}$)

PARAMETER		SYMBOL	TEST CONDITION		V _{CC} (V)	MIN.	MAX.	UNIT
Input Voltage	"H" Level	V _{IH}			2.3~2.7	1.6	—	V
	"L" Level	V _{IL}			2.3~2.7	—	0.7	
Output Voltage	"H" Level	V _{OH}	V _{IN} = V _{IH} or V _{IL}	I _{OH} = - 100μA	2.3~2.7	V _{CC} - 0.2	—	V
				I _{OH} = - 6mA	2.3	2.0	—	
				I _{OH} = - 12mA	2.3	1.8	—	
				I _{OH} = - 18mA	2.3	1.7	—	
	"L" Level	V _{OL}	V _{IN} = V _{IH} or V _{IL}	I _{OL} = 100μA	2.3~2.7	—	0.2	
				I _{OL} = 12mA	2.3	—	0.4	
				I _{OL} = 18mA	2.3	—	0.6	
Input Leakage Current		I _{IIN}	V _{IN} = 0~3.6V	2.3~2.7	—	± 5.0	μA	
3-State Output Off-State Current		I _{OZ}	V _{IN} = V _{IH} or V _{IL} V _{OUT} = 0~3.6V	2.3~2.7	—	± 10.0	μA	
Power Off Leakage Current		I _{OFF}	V _{IN} , V _{OUT} = 0~3.6V	0	—	10.0	μA	
Quiescent Supply Current		I _{CC}	V _{IN} = V _{CC} or GND	2.3~2.7	—	20.0	μA	
			V _{CC} ≤ (V _{IN} , V _{OUT}) ≤ 3.6V _{CC}	2.3~2.7	—	± 20.0		

PRELIMINARY

ELECTRICAL CHARACTERISTICS

DC characteristics (Ta = -40~85°C, 1.8V ≤ V_{CC} < 2.3V)

PARAMETER		SYMBOL	TEST CONDITION			MIN.	MAX.	UNIT	
			V _{CC} (V)						
Input Voltage	“H” Level	V _{IH}				1.8~2.3	0.7 × V _{CC}	V	
	“L” Level	V _{IL}				1.8~2.3	—		
Output Voltage	“H” Level	V _{OH}	V _{IN} = V _{IH} or V _{IL}	I _{OH} = - 100μA	1.8	V _{CC} - 0.2	—	V	
				I _{OH} = - 6mA	1.8	1.4	—		
	“L” Level	V _{OL}	V _N = V _{IH} or V _{IL}	I _{OL} = 100μA	1.8	—	0.2		
				I _{OL} = 6mA	1.8	—	0.3		
Input Leakage Current		I _{IIN}	V _{IN} = 0~3.6V			1.8	—	± 5.0	μA
3-State Output Off-State Current		I _{OZ}	V _{IN} = V _{IH} or V _{IL} V _{OUT} = 0~3.6V			1.8	—	± 10.0	μA
Power Off Leakage Current		I _{OFF}	V _{IN} , V _{OUT} = 0~3.6V			0	—	10.0	μA
Quiescent Supply Current		I _{CC}	V _{IN} = V _{CC} or GND			1.8	—	20.0	μA
			V _{CC} ≤ (V _{IN} , V _{OUT}) ≤ 3.6V			1.8	—	± 20.0	

AC characteristics (Ta = -40~85°C, Input t_r = t_f = 2.0ns, C_L = 30pF, R_L = 500Ω)

PARAMETER		SYMBOL	TEST CONDITION		V _{CC} (V)	MIN.	MAX.	UNIT
Propagation Delay Time		t _{pLH} t _{pHL}	(Fig.1, 2)		1.8	1.5	TBD	ns
					2.5 ± 0.2	1.0	TBD	
					3.3 ± 0.3	0.8	TBD	
3-State Output Enable Time		t _{pZL} t _{pZH}	(Fig.1, 3)		1.8	1.5	TBD	ns
					2.5 ± 0.2	1.0	TBD	
					3.3 ± 0.3	0.8	TBD	
3-State Output Disable Time		t _{pLZ} t _{pHZ}	(Fig.1, 3)		1.8	1.5	TBD	ns
					2.5 ± 0.2	1.0	TBD	
					3.3 ± 0.3	0.8	TBD	
Output To Output Skew		t _{osLH} t _{osHL}	(Note 11)		1.8	—	TBD	ns
					2.5 ± 0.2	—	TBD	
					3.3 ± 0.3	—	TBD	

For C_L = 50pF, add approximately 300ps to the AC maximum specification.

(Note 11) Parameter guaranteed by design.

$$(t_{osLH} = |t_{pLHm} - t_{pLHn}|, t_{osHL} = |t_{pHLm} - t_{pHLn}|)$$

Dynamic switching characteristics (Ta = 25°C, Input $t_r = t_f = 2.0\text{ns}$, $C_L = 30\text{pF}$)

PARAMETER	SYMBOL	TEST CONDITION	V _{CC} (V)	TYP.	UNIT
Quiet Output Maximum Dynamic V _{OL}	V _{OLP}	V _{IH} = 1.8V, V _{IL} = 0V (Note 12)	1.8	TBD	V
		V _{IH} = 2.5V, V _{IL} = 0V (Note 12)	2.5	TBD	
		V _{IH} = 3.3V, V _{IL} = 0V (Note 12)	3.3	TBD	
Quiet Output Minimum Dynamic V _{OL}	V _{OLV}	V _{IH} = 1.8V, V _{IL} = 0V (Note 12)	1.8	TBD	V
		V _{IH} = 2.5V, V _{IL} = 0V (Note 12)	2.5	TBD	
		V _{IH} = 3.3V, V _{IL} = 0V (Note 12)	3.3	TBD	
Quiet Output Minimum Dynamic V _{OH}	V _{OHV}	V _{IH} = 1.8V, V _{IL} = 0V (Note 12)	1.8	TBD	V
		V _{IH} = 2.5V, V _{IL} = 0V (Note 12)	2.5	TBD	
		V _{IH} = 3.3V, V _{IL} = 0V (Note 12)	3.3	TBD	

(Note 12) Parameter guaranteed by design.

Capacitive characteristics (Ta = 25°C)

PARAMETER	SYMBOL	TEST CONDITION	V _{CC} (V)	TYP.	UNIT
Input Capacitance	C _{IN}	—	1.8, 2.5, 3.3	TBD	pF
Output Capacitance	C _{OUT}		1.8, 2.5, 3.3	TBD	pF
Power Dissipation Capacitance	C _{PD}	f _{IN} = 10MHz (Note 13)	1.8, 2.5, 3.3	TBD	pF


(Note 13) C_{PD} is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load.

Average operating current can be obtained by the equation :

$$I_{CC}(\text{opr.}) = C_{PD} \cdot V_{CC} \cdot f_{IN} + I_{CC}/4 \text{ (per gate)}$$

PRELIMINARY

Fig.1 Test Circuit



PRELIMINARY

AC WAVEFORM

Fig.2 t_{pLH} , t_{pHL}





Fig.3 t_{pLZ} , t_{pHZ} , t_{pZL} , t_{pZH}





SYMBOL	VCC		
	3.3 ± 0.3V	2.5 ± 0.2V	1.8V
V _{IH}	2.7V	V _{CC}	V _{CC}
V _M	1.5V	V _{CC} / 2	V _{CC} / 2
V _X	V _{OL} + 0.3V	V _{OL} + 0.15V	V _{OL} + 0.15V
V _Y	V _{OH} - 0.3V	V _{OH} - 0.15V	V _{OH} - 0.15V



OUTLINE DRAWING

TSSOP14-P-0044-0.65

Unit : mm



PRELIMINARY



Weight : 0.06g (Typ.)