
DB LECTRO Inc.


B33 FEMALE HEADER
PROFILE : 6.4mm SMT TYPE
PITCH: 2.0mm

SPECIFICATIONS


Material
Insulator : Nylon 6T, glass reinforced, rated UL 94V-0
Contact : Phosphor Bronze


Electrical
Current Rating : 1 Amp DC
Contact Resistance : 30 mΩ max.
Insulation Resistance : 3000 MΩ min.
Dielectric Withstanding Voltage : 500V AC for 1minute
Operating Temperature : -40℃ to +105℃
• Mating Suggestion : C29, C30 series.














RECOMMENDED P.C.B LAYOUT

HOW TO ORDER:

B33 - 1 - 2 - 3 - 4

1.NO. OF CONTACT	2.CONTACT MATERIAL	3.CONTACT PLATING	4.INSULATOR COLOR
DUAL ROW 2*2 - 2*40	B: PHOSPHOR BRONZE	T: TIN PLATED S: SELECTIVE G: GOLD FLASH A: 5u" INCH GOLD B: 10u" INCH GOLD C: 15u" INCH GOLD D: 30u" INCH GOLD	1. BLACK

3600 boul. Matte suite i Brossard Qc J4Y-2Z2 tel:(450)-444-1424 fax:(450)-444-4714