ADELS contact

Transformer Connectors

DK 4 O grey



Feed-through Connector, 1 pole, grey, Voltage Rating: 500 V, Cross-Section: 4.0 mm²

Order Info

Reference Number (ref. no.)	202101
Applications	Transformers
PU	500
EAN	4028012108428

Type

Type	Feed-through Connector
Number of poles	1 pole
Clamping Units per Pole	1
Colour	grey
Cross-Section	4.0 mm²
Connection Type	Löt-Schraub

Technical Data

Voltage Rating	500 V
Current Rating	32 A
Insulating Material	PA 6.6
Contact Material	Brass
Core Cross-Section min.	0.5 mm²
Core Cross-Section max.	4.0 mm²
Flammability Rating	V-2
max. Ambient Temperature Operation	85 °C
Type of Conductor Solid	yes
Type of Conductor Flexible	yes
Type of Conductor Stranded	yes
Stripping Length	8.5-9.0 mm
Assembly Contact Screw	0.8x4.0 / ↻ 0.8 Nm
Wall Thickness min.	1.2 mm
Wall Thickness max.	4.0 mm
Housing Hole Diameter	7,2 (-0,1) mm
Pin Spacing	10.0 mm
Approbation UL	DK4_DK4Si_19980630_UL_E63492_1-16_Description_web.pdf

Approbation CSA	Trafoklemmen_20160615_CSA_70073973_Certificate_web.pdf

Accessories

BZ 14 RU	293800
BZ 14 U	293300