Part Number: 34250-0002

Status: Active

Overview: MX150™ Sealed and Unsealed Connector System

Description: MX150™ Cable Sealed Female Connector, Single Row, 3 Circuits, Polarization B, with Connector Position Assurance, Gray

Series

image - Reference only

Documents:

Drawing (PDF)
Product Specification PS-34250-000 (PDF)
Product Specification PS-34646-001 (PDF)
Application Specification AS-34250-100 (PDF)
RoHS Certificate of Compliance (PDF)

General

Product Family	Crimp Housings
Series	34250
Application	Power
Comments	with Connector Position Assurance (CPA), Dual Key
More Detailed Tech Information	http://ewcap.uscarteams.org
Overview	MX150™ Sealed and Unsealed Connector System
Product Name	MX150™
UPC	756054705049

Physical

Circuits (maximum)	3
Circuits Detail	3
Color - Resin	Gray
Gender	Female
Glow-Wire Compliant	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Resin	Polyester, Polyphenylene Ether Alloy
Net Weight	7.280/g
Number of Rows	1
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	4.50mm
Pitch - Termination Interface	4.50mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40°C to +125°C

Electrical

Current - Maximum per Contact	15A

Material Info

Reference - Drawing Numbers

Application Specification	AS-34250-100
Product Specification	PS-34250-000, PS-34646-001
Sales Drawing	SD-34250-002

EU RoHS
ELV and RoHS Compliant
REACH SVHC
Not Reviewed
Low-Halogen Status
Low-Halogen

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series
34250Series

Mates With
Direct Connect only

Use With
34083 Tin (Sn) Cable Seal Female Terminal, 34081 Gold (Au) Cable Seal Female Terminal