

MPV5 Series
9x14 mm, 5.0 Volt, PECL, VCXO



- LVDS and PECL Output Logic With Good Integrated Jitter Performance (5 ps)
- Phase-Locked Loops (PLL's), Clock Recovery, Reference Signal Tracking, Synthesizers, Frequency Modulation/ Demodulation

Ordering Information

MPV510R1PJ00.0000 MHz

Product Series

Temperature Range

Stability

Output Type

Absolute Pull Range

Symmetry/Output Logic Type

Package/Lead Configurations

Frequency (customer specified)

1: 0°C to +70°C

2: -40°C to +85°C

6: -20°C to +70°C

8: 0°C to +50°C

0: Nominal per APR selection

R: Complementary, Tri-state

T: Single, Tri-state

Z: Complementary, Non Tri-state

X: Single, Non Tri-state

1: ±50 ppm (±35 ppm typ. Stability)

2: ±100 ppm (±20 ppm typ. Stability)


5: ±80 ppm (±25 ppm typ. Stability)

8: ±25 ppm (±50 ppm typ. Stability)



P: 45/55% PECL

Q: 40/60% PECL

J: J-lead




OBSOLETE




Pin Connections

PIN	FUNCTION
1	Control Voltage
2	Tri-state or N/C
3	Ground/Case
4	Output Q
5	Output $\overline{Q}$ or N/C
6	+Vcc



All dimensions
in inches (mm).

SUGGESTED SOLDER PAD LAYOUT



M-tron reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of such product.

MPV5 Series

9x14 mm, 5.0 Volt, PECL, VCXO



	PARAMETER	Symbol	Min.	Typ.	Max.	Units	Condition
Electrical Specifications	Frequency Range	F	0.75		800	MHz	See Note 1
	Frequency Stability	$\Delta F/F$	(See Ordering Information)				See Note 2
	Operating Temperature	Ts	-40		+85	°C	See ordering info.
	Storage Temperature	Ta	-55		+125	°C	
	Input Voltage	Vcc	4.75	5.0	5.25	V	
	Input Current	Idd					
	0.75 MHz to 24 MHz				60	mA	
	24 MHz to 160 MHz				100	mA	
	160 MHz to 800 MHz				120	mA	
	Symmetry (Duty Cycle)		40	50	60	%	@ Vcc -1.3 VDC
	Load						See Note 3
	Rise/Fall Time	Tr/Tf		.35	.55	ns	@ 20/80%
	Logic Level						
	Logic Level						
	Cycle time						
	@ 38.88 MHz			5		ps RMS	Sigma
	@ 155.52 MHz						
	@ 622.08 MHz			10	20	ps RMS	
	Phase Jitter	ϕJ					Integrated 12 kHz - 20 MHz
	@ 38.88 MHz			.3	.5	ps RMS	
	@ 155.52 MHz			3	5	ps RMS	
	@ 622.08 MHz			3	5	ps RMS	
Environmental	Peak to Peak Jitter (+/-)	Tj					@ BER 1E-12
	@ 38.88 MHz			2.1	3.5	ps RMS	
	@ 155.52 MHz			21	35	ps RMS	
	@ 622.08 MHz			21	35	ps RMS	
	Phase Noise (Typical)						Offset from carrier
	@ 38.88 MHz	10 Hz	100 Hz	1 kHz	10 kHz	100 kHz	dBc/Hz
	@ 155.52 MHz	-65	-97	-127	-143	-153	dBc/Hz
	@ 622.08 MHz	-50	-80	-112	-128	-125	dBc/Hz
		-50	-80	-110	-123	-120	dBc/Hz
	Modulation Bandwidth	fm			10k	Hz	-3 dB bandwidth
	Input Impedance	Zin	50			K Ω	
	Control Voltage	Vcc	0.5	2.5	5	V	Pin 1 voltage
	Center Frequency	Vc0		2.5		V	
	Linearity			5	10	%	
	Pullability	APR	(See Ordering Information)				See Note 4
	Tri-state Output "On"	OE	2.8			V	Pin 2 voltage
	Tri-state Output "Off"	OE			0.6	V	Pin 2 voltage
	Mechanical Shock	Per MIL-STD-202, Method 213, Condition C					
	Vibration	Per MIL-STD-202, Method 201 & 204					
	Reflow Solder Conditions	See "Figure 2" on page 147					
	Hermeticity	Per MIL-STD-202, Method 112 (1 x 10 ⁻⁸ atm.cc/s of helium)					
	Solderability	Per MIL-STD-883, Method 2003					

1. Frequencies above 70 MHz utilize a PLL design. Fundamental and PLL designs are available for other frequencies. Contact factory.
2. Stability is given for deviation over temperature.
3. PECL load - see load circuit diagram #3 on page 148.
4. APR specification inclusive of initial tolerance, deviation over temperature, shock, vibration, supply voltage, and aging.

M-tron reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of such product.

M-tron Industries, Inc., PO Box 630, Yankton, SD 57078-0630, USA Phone: 605-665-9321 or 1-800-762-8800 Fax: 605-665-1709 Website: www.mtron.com
M-tron Industries Limited, 1104 Shanghai Industrial Investment Building, 48-62 Hennessy Road, Wanchai, Hong Kong, China Phone: 852-2866-8023 Fax: 852-2529-1822