



PCB HOLES(THE PATTERN SIDE) t=1.6mm
NOTE:GENERAL TOLERANCE:±0.1mm

电气特性:Electrical:

- 额定电流: Current Rating
1.5A/contact terminal
- 额定电压: Voltage Rating
30V DC
- 接触阻抗:Contact Resistance
30 milliohms MAX
- 耐电压:Dielectric Withstanding Voltage:
500 V AC AT Sea Level
- 绝缘阻抗:Insulation Resistance:
1000MEGA ohms MIN

物理性能:Mechanical:

- 插拔力: Connector Mate and Umate Force
Mate force:3.57kgf (MAX)
Umate force:1.02kgf (MIN)
- 端子保持力: Terminal Retention
1.2kgf (MIN)
- 寿命: 1500次
- 原材料:Material:
1. 塑胶:Housing:PBT NC
2. 端子>Contact:Copper Alloy C2680
3. 外壳:Shell:SPCC
- 电镀:Finish:
1. 端子Contact: Au 0.7u" Plated on contact area
Tin50u" Plated on solder area
Nickel 50u" Plated underplating over all.
2. 外壳Shell: Nickel 50u"Min plating over all.

产品图
PRODUCT CHART DWG

深圳市精拓金电子有限公司

Pin NUMBER	SIGNAL NAME
1	VBUS
2	D-
3	D+
4	GND

公差一览表
TOLERANCE UNLESS OTHERWISE

公差	公差	公差	公差
1	2	3	4
±0.25	±0.20	±0.15	±0.10
X'	X'	XX'	XXX'

公差	公差	公差	公差
1	2	3	4
±5'	±2'	±1'	±0.5'
X'	X'	XX'	XXX'

单位	MM	制图	林属升	产品料号	909-281A101SD10100
比例	1:1	审核	郭志富	产品名称	AF10.08英寸后两脚无边铁壳PBT白胶
日期	2015/10/20	核准	黄国荣	角法	7.80DIP无耳架
DATE		APD		版本	VER
				A0	