# **Ultra High Performance BGA Cooling Solutions** w/ Thermal Tape Attachment





ATS Part#: Description:

#### ATS-52300G-C1-R0

maxiFLOW<sup>™</sup> Heat Sink, T412, BLUE-ANODIZED

Heat Sink Type: maxiFLOW Heat Sink Attachment: Equivalent Part Number: ATS-52300G-C2-R0

THERMAL TAPE

\*Image above is for illustration purpose only.

#### **Features & Benefits**

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low .
- . Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks
- Comes pre-assembled with high performance thermal interface material ٠

### **Thermal Performance**

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	4.38 °C/W	3.56 °C/W	3.09 °C/W	2.77 °C/W	2.54 °C/W	2.36 °C/W	2.21 °C/W
	Ducted Flow	3.58	n/a	n/a	n/a	n/a	n/a	n/a

## **Product Detail**

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	30.0 mm	30.0 mm	12.5 mm	53.3 mm	T412	BLUE-ANODIZED
	<ul> <li>Dimensior</li> <li>ATS-5230 (Saint Gol</li> <li>Thermal p application</li> <li>ATS reserve performant</li> <li>ATS certification</li> </ul>	ves the right to upda	eight from the botton act heat sink assemi provided for referen ate or change its pro k assembly is RoHS	oly with an equivalen nce only. Actual perf ducts without notice -6 and REACH com	t thermal ormance to improv	interface material may vary by
*Image above is for illustration purpose only.						

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2012 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA