


	X	Y
0.75~1.25	30.0+0.1	122.0+0.1
1.25~2.00	30.2+0.1	122.0+0.1
2.00~3.00	30.4+0.1	122.0+0.1



**MATERIAL:**

Body:Nylon66, UL rated:94V-2 min

Actuator:Nylon66, UL rated:94V-2 min

Terminal:Brass, silver or tin plated

Rating: 40A 125V AC

25A 250V AC

Function:ON-ON

Contact Resistance:50mΩ Max

Insulation Resistance:DC 500V 100MΩ Min

Dielectric Strength:2000VAC 1 minute

Electrical life:10,000 cycles

Mechanical life :50,000 cycles

Operating Temperature:-20℃~85℃

Safety Approval:

公差 TOLERANCES	.X±0.3	.XX±0.15	角度 ANGLE	±1°	单位	DIMENSION UNIT	mm.
---------------	--------	----------	----------	-----	----	----------------	-----



**D-SWITCH**  
东莞市德松电子有限公司  
D-SWITCH ELECTRONICS CO.,LTD

版本 VER	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	核准 APPROVED BY	核对 CHECKED BY	绘图 DRAWN BY	品名 TITLE	图号 DRAWING NO
A 1	整理图画	2013.3.18				吴润成	R-6-220-C5N-BR	1040004